



Product Code: LC24P2X12-65

IDE LC24P2X12-65 Transparent Lid With E+N Bars 12-Module 2-Row Halogen-Free Plastic RAL 7035 Grey Surface Mount IP65

- IP65 protection for harsh environments
- Halogen-free plastic construction
- Rated voltage of 1500 VDC
- Transparent tinted polycarbonate lid
- Top, bottom, oblong rear cable entry

Specifications

Product Type	Load Centre
Brand	IDE
Ambient Temperature	-25 to 40 deg C
Ball Pressure Test	70 deg C
Cable Entry	Top, Bottom, Oblong Rear
Colour	RAL 7035 Light Grey
Degree of Protection	IP65
Depth	148 mm
Height	436 mm
Insulation Class	Class II (Double Insulation)
Lid Material	Tinted PC
Material	Halogen-Free Plastic
Mounting Type	Surface
Number of Modules	12
Number of Rows	2
Rated Current	125 A
Rated Impact Resistance	IK08
Rated Voltage	1500 VDC
Standards and Approvals	IEC 62208, Directive 2014/35/EU, AS/NZS 61439.3:2016 Appendix ZZ Clauses 10.101 and 10.102, AS/NZS 3000 Clause 2.10.4.2, IEC 62208 Directive 2014 35/EU Compliant
Weight	2.37 kg
Width	310 mm
Window Type	Transparent
Width(mm)	310

Height(mm) 436

Depth(mm) 148

Drawing

