




Enclosed Links from 100 - 840A

Rating A	Holes	Part Number	Cover Colour	Depth mm	Width mm	Length mm	Mounting D = DIN P = Panel	Sealable
100	5	A100/5	Black	49	50	69	P	Y
	5	A100/5R	Red	49	50	69	P	Y
	7	A100/7	Black	49	50	100	P	Y
	7	A100/7R	Red	49	50	100	P	Y
	10	A100/10	Black	49	50	100	P	Y
	10	A100/10R	Red	49	50	100	P	Y
100	4	NSWLINK	Black	69	56	82	P	Y
	4	VICLINK	Black	69	56	82	P	Y
125	8	DB35	Grey	46	27	75	D/P	N
140	3	T3140B	Black	52	46	65	P	Y
	3	T3140R	Red	52	46	65	P	Y
165	7	A165/7	Black	41	42	99	P	Y
	7	A165/7R	Red	41	42	99	P	Y
	7	A165/7BW	Black	41	42	99	P	Y
	7	A165/7BWR	Red	41	42	99	P	Y
	7	LT165/7	Cream	49	49	109	P	Y
310	10	FSPDB3C	Grey	64	47	101	D/P	N
335	2	FSPDB4C	Grey	80	39	146	D/P	N
350	7	A350/7	Black	52	46	120	P	Y
	7	A350/7R	Red	52	46	120	P	Y
	13	A350/13	Black	52	46	120	P	Y
	13	A350/13R	Red	52	46	120	P	Y
	7	LT350/7	Cream	58	60	131	P	Y
840	4	FSPDB5C	Grey	80	72	145	P	N

**A100/5****A100/7R****A100/10****NSWLINK****VICLINK****DB35****T3140R****A165/7****A165/7BW**



Enclosed Links from 100 - 840A

Rating A	Holes	Part Number	Hole size & quantity										
			5	6	7	8	9	12	15	20	24	Line Taps	
			Recommended maximum cable size										
			10mm²	16mm²	25mm²	35mm²	50mm²	70mm²	120mm²	185mm²	300mm²	35mm²	120mm²
100	5	A100/5		3	2								
	7	A100/7		4	3								
	10	A100/10		7	3								
100	4	NSWLINK	1		1		2						
	4	VICLINK	1		1		2						
125	8	DB35	6	1		1							
140	3	T3140B				3							
165	7	A165/7		2	2	1		2					
	7	A165/7BW		2	2	1		2					
	7	LT165/7		3		2						2	
310	10	FSPDB3C				8		1		1			
335	2	FSPDB4C								2			
350	7	A350/7		1		2		2	2				
	13	A350/13	2	8		1			2				
	7	LT350/7		1		2	2						2
840	4	FSPDB5C									4		

Accessories for FS links

FSCAP2 - Sealingcap for spare spaces up to 185mm²

FSPIN1 - Multipole pins to join blocks

FSCAP3 - Sealingcap for spare spaces up to 300mm²



LT165/7



FSPDB3C



FSPBB4C



A350/7



A350/13R



LT350/7



FSPDB5C



ACCESSORIES