



Your Industrial Products solution *

Spec Sheet: Red Spot Fuse Fitting 100A

- Insulating sleeves to protect cable entry.
 - Full shrouded contacts, IP20 degree of protection.
 - Made from tough flame retardant non-hydroscopic material.
 - Anti-vibration contact design.
 - Interference fit contacts for low watts loss.

Standards

Australian Standard AS60269 and BS88 Part 2, ASTA, CSA



Range

	Rated current (Ie)	100A	Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
	Rated voltage (Ue)	690V	100A	Front Wire	Black	5	RS100H
Rated peak withstand current	80kA	2 Stud rear	Black	RS100P			
Rated impulse withstand voltage (Uiimp)	8kV	Busbar / Front wire	Black	RS100PH			
Screw mounting size (all)	M6	Back Wire	Black	RS100BW			
Weight 1P (Front wire)	0.78kg	Front Wire	White	RS100HWH			
Max Cable Size (front)	95mm ²	2 Stud rear	White	RS100PWH			
Max Cable Size (rear)	70mm ²	Solid Neutral Link	-	RS100CLINK			
Maximum tightening torque (front)	3.5-4Nm	Padlock barrier	Yellow	3	RS100LOCK		
Fuse type (suit all)	TCP_						

Dimensions

