



Your Industrial Products solution \*

## Spec Sheet: Red Spot Fuse Fitting 20A

- Insulating sleeves to protect cable entry.
- Full shrouded contacts, IP20 degree of protection.
- Made from tough flame retardant non-hydroscopic material.
- Anti-vibration contact design.
- Optional DIN rail mounting bracket.

### Standards

Australian Standard AS60269 and BS88 Part 2, ASTA, CSA



### Range

<b>Rated current (Ie)</b>	20A
<b>Rated voltage (Ue)</b>	690V
<b>Rated peak withstand current</b>	80kA
<b>Rated impulse withstand voltage (Uiimp)</b>	8kV
<b>Screw mounting size (all)</b>	M5
<b>Weight 1P (Front wire)</b>	0.1kg
<b>Max Cable Size (front / rear)</b>	10mm <sup>2</sup>
<b>Maximum tightening torque (front)</b>	1.5-2Nm
<b>Fuse type (suit all)</b>	NIT_

Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
20A	Front Wire	Black	10	RS20H
	Busbar / Front wire	Black		RS20P
	2 Stud rear	Black		RS20PH
	Back Wire	Black		RS20BW
	Front Wire	White		RS20HWH
	2 Stud rear	White		RS20PWH
	Solid Neutral Link	-		RS20CLINK
	Padlock barrier	Yellow	3	RS20LOCK
-	Protective Boot – suit rear stud	Black	10	RS20/32S

### Dimensions

