



Your Industrial Products solution *

Spec Sheet: RS Fuse Fitting 63A

- Insulating sleeves to protect cable entry.
- Full shrouded contacts, IP20 degree of protection.
- Made from tough flame retardant non-hydroscopic material.
- Anti-vibration contact design.
- Tapered shank on fuse fixing screws, easy re-entry.

Standards

Australian Standard AS60269



Range

Rated current (Ie)	63A	Rated Current (A)	Type of Connection	Colour	Pack Quantity	Catalogue Number
Rated voltage (Ue)	690V					
Rated peak withstand current	80kA		Front Wire	Black		RS63H
Rated impulse withstand voltage (Uiimp)	8kV		Busbar / Front wire	Black		RS63PH
Screw mounting size (all)	M5		2 Stud rear	Black		RS63P
Weight 1P (Front wire)	0.32kg		Back Wire	Black		RS63BW
Max Cable Size (front)	50mm ²		Front Wire	White		RS63HWH
Max Cable Size (rear)	35mm ²		2 Stud rear	White		RS63PWH
Maximum tightening torque (front)	2.5-3Nm		Solid Neutral Link	-		RS63CLINK
Fuse type (suit all)	TIA/TIS_		Padlock barrier	Yellow	3	RS63LOCK

Dimensions

