



Data subject to change without notice. Always confirm the data is correct from the seller.

# KEA 325 YR A2

## KEA Aluminium 16-250A

- IP66; Enclosure types A2, A4
- IP65; Enclosure types A5, A6
- IK08; A2, A4 (Degree of mechanical impact)
- IK10: A5, A6
- Excellent for hard weather conditions
- Wide operating temperature range
- Good resistance against many chemicals
- Good UV resistance
- Padlockable
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

**Technical datasheet >>**

Accessories



## Product details

<b>SKU</b>	KEA 325 YR A2
<b>AC-21 400/415 V (A)</b>	40 A
<b>AC-21 690 V (A)</b>	40 A
<b>AC-22 400/415 V (A)</b>	25 A
<b>AC-22 690 V (A)</b>	25 A
<b>AC-23 400/415 V (A/kW)</b>	25 A / 11 kW
<b>AC-23 690 V (A/kW)</b>	25 A / 22 kW
<b>Cable Area to Switch Terminal (only Cu) (mm<sup>2</sup>) / Bolt size</b>	1.5-16
<b>Color</b>	Yellow / Red
<b>EAN</b>	6419410330241
<b>Enclosure</b>	A2
<b>Enclosure Type</b>	Aluminium
<b>IP Rating</b>	66
<b>Number of Poles</b>	3
<b>Operation</b>	Front-operated
<b>Switch type</b>	Load Break Switch
<b>Weight (kg)</b>	0.8

## Dimensional drawing

