



Data subject to change without notice. Always confirm the data is correct from the seller.

# KER 363 YR RA4

## KER Stainless Steel 16-1600A

- IP66; AISI 316 Enclosure types RA2, RA4, RA5
- IP66; AISI304 Enclosure types R6, R7, R8, R9, R10 (AISI 304 as standard, AISI 316 upon request)
- Where hygiene and good protection against corrosion are required
- Padlockable with three locks
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- Also available as EMC, and EMC/EX-protected
- **Note!** AI-cables cannot be connected directly to switch terminals. For AI-cable connection please use a bi-metal cable connector, **available here**.

### Technical datasheet >>

Accessories



## Product details

<b>SKU</b>	KER 363 YR RA4
<b>AC-21 400/415 V (A)</b>	80 A
<b>AC-21 690 V (A)</b>	80 A
<b>AC-22 400/415 V (A)</b>	63 A
<b>AC-22 690 V (A)</b>	63 A
<b>AC-23 400/415 V (A/kW)</b>	40 A / 22 kW
<b>AC-23 690 V (A/kW)</b>	40 A / 37 kW
<b>Cable Area to Switch Terminal (only Cu) (mm2) / Bolt size</b>	2.5-35
<b>Color</b>	Yellow / Red
<b>EAN</b>	6419410343579
<b>Enclosure</b>	RA4
<b>Enclosure Type</b>	Stainless Steel: Polycarbonate Handle
<b>IP Rating</b>	66
<b>Number of Poles</b>	3
<b>Operation</b>	Front-operated
<b>Switch type</b>	Load Break Switch
<b>Weight (kg)</b>	2.3

## Dimensional drawing

