



Data subject to change without notice. Always confirm the data is correct from the seller.

KER 416 YR RA2

KER Stainless Steel 16-1600A

- IP66; AISI 316 Enclosure types RA2, RA4, RA5
- IP66; AISI304 Enclosure types R6, R7, R8, R9, R10 (AISI 304 as standard, AISI 316 upon request)
- Where hygiene and good protection against corrosion are required
- Padlockable with three locks
- Door interlock with defeat mechanism
- Tested according to IEC 60947-3
- Also available as EMC, and EMC/EX-protected
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here**.

Technical datasheet >>

Accessories



Product details

SKU	KER 416 YR RA2
AC-21 400/415 V (A)	25 A
AC-21 690 V (A)	25 A
AC-22 400/415 V (A)	16 A
AC-22 690 V (A)	16 A
AC-23 400/415 V (A/kW)	16 A / 7.5 kW
AC-23 690 V (A/kW)	16 A / 11 kW
Cable Area to Switch Terminal (only Cu) (mm2) / Bolt size	1.5-16
Color	Yellow / Red
EAN	6419410343159
Enclosure	RA2
Enclosure Type	Stainless Steel: Polycarbonate Handle
IP Rating	66
Number of Poles	4
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	1.3

Dimensional drawing

