




SKINTOP® MS-M-XL / SKINTOP® MSR-M-XL

**Benefits****SKINTOP® MS-M-XL**

- Especially for thick walls
- Maximum reliability
- Optimum strain relief
- Wide, variable clamping ranges

SKINTOP® MSR-M-XL

- For the benefits, refer to SKINTOP® MS-M-XL

Application range**SKINTOP® MS-M-XL**

- With long connection thread for applications involving a thicker wall.

SKINTOP® MSR-M-XL

- With reducing seal insert, to seal cables with smaller outer diameters.

Norm references / Approvals

- UL File Nr. E79903

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information EN 50262

Note

- Counter nut to be used: SKINDICHT® SM-M
- Refer to SKINTOP® metric accessories for suitable accessories

Technical data**Classification**

ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description:
Cable screw gland

**Caution**

Refer to Appendix T21 for the installation dimensions and torques

**Material**

Body: nickel-plated brass
Insert: polyamide
Sealing ring: CR
O-ring: NBR

**Protection rating**

IP 68 - 10 bar
IP 69

**Temperature range**

dynamic -25°C up to + 100°C
Fixed: -40°C to + 100°C

Article number	Article designation / size	Clamping range ØF (mm)	SW wrench size mm	Overall length, C (mm)	Thread length, D (mm)	Pieces / PU
SKINTOP® MS-M-XL						
53112005	12 x 1,5	3-7	16	32.8	12	100
53112015	16 x 1,5	4,5-10	20	37.0	12	50
53112025	20 x 1,5	7-13	24	39.5	12	50
53112035	25 x 1,5	9-17	29	41.5	12	25
53112045	32 x 1,5	11-21	36	48.2	15	25
53112055	40 x 1,5	19-28	45	53.5	15	10
53112065	50 x 1,5	27-35	54	57.0	15	5
SKINTOP® MSR-M-XL						
53112105	12 x 1,5	1-5	16	32.8	12	100
53112115	16 x 1,5	2-7	20	37.0	12	50
53112125	20 x 1,5	5-10	24	39.5	12	50
53112135	25 x 1,5	6-13	29	41.5	12	25
53112145	32 x 1,5	7-15	36	48.2	15	25
53112155	40 x 1,5	15-23	45	53.5	15	10
53112165	50 x 1,5	22-29	54	57.0	15	5

Photographs are not to scale and do not represent detailed images of the respective products.