

domestic fuse carriers



Dimensions see p. 145

With label-holders
With insulated carrier class II, padlockable
Coupling via supply busbars
Shielded terminals capacity 2 x 10 mm²
Possibility to signal indicator blown fuse
Fuse not supplied

Pack	Cat.No.	For domestic cylindrical cartridge fuses		
		Conform to EN 60269-1 and IEC 60269-1,3		
		Single pole		
		For domestic cartridges	Cartridge dimensions (mm)	Number of modules
10	058 10	10 A - 230 V~	8.5 x 23	1
10	058 11	16 A	10.3 x 25.8	1
10	058 12	20 A - 400 V~	8.5 x 31.5	1
10	058 13	25 A	10.3 x 31.5	1
10	058 14	32 A	10.3 x 38	1
		Single pole + neutral		
10	058 20	10 A - 230 V~	8.5 x 23	1
10	058 21	16 A	10.3 x 25.8	1
10	058 22	20 A - 400 V~	8.5 x 31.5	1
10	058 24	32 A	10.3 x 38	1

		For miniature cylindrical cartridge fuses		
		Conform to EN 60127-6 and IEC 60127-6 To protect sensitive equipment: transformers, electronic equipment, etc.		
		Single pole		
		Cartridge dimensions (mm)	Voltage	Number of modules
5	058 00	5 x 20	250 V~	1

domestic cartridge fuses



Pack	Cat.No.	Miniature type 5 x 20		
		Instant reaction fuse - Ceramic body Conform to EN/IEC 60127-2 High rupture capacity (A) For use with dimmers, Viking terminal blocks and emergency lightning units, transformers		
		Rating (Amps)	Voltage ~ (Volts)	Breaking capacity (Amps)
10	102 02	0.2		
10	102 05	0.5		
10	102 06	0.63		
10	102 10	1		
10	102 20	2	250	1500
10	102 30	3.15		
10	102 50	5		
10	102 63	6.3		
10	102 96 ¹	10	250	500

		Cylindrical				
		6.3 x 23				
		Without indicator	Rating (Amps)	Voltage ~ (Volts)	Rupture capacity (Amps) Copper	Protected section (mm ²)
10	103 06 ²	6	230	6000	1.5	
		8.5 x 23				
10	113 10	10	230	6000	1.5	
		10.3 x 25.8				
10	116 10 ²	10	230	6000		
10	116 16 ²	16			2.5	
		8.5 x 31.5				
10	123 20	20	400	20000	2.5	
		10.3 x 31.5				
10	126 16	16				
10	126 20	20	400	20000		
10	126 25	25			4	
		10.3 x 38				
10	133 32	32	400	20000		

		Neutral links	
10	123 00	8 x 32 (previously 8.5 x 31.5)	
10	133 00	10 x 38	

1: Overrating not described by standards
2: Conform to BS 1361 (1971)

isolating fuse carriers



058 06



058 28



058 48



043 83



Dimensions see p. 145

For industrial cylindrical cartridge fuses type aM or gG

Conform to standard IEC 60269-2
Isolators conform to IEC 60947-3
Icc:
- 20 kA with 8.5 x 31.5 cartridge fuse
- 100 kA with 10 x 38 cartridge fuse
Fuse not supplied (see opposite)

Single pole

Cartridge dimensions (mm)	Voltage	Number of modules
8.5 x 32	400 V~	1
10 x 38	500 V~	1

Single pole + neutral

10 x 38	500 V~	1
---------	--------	---

2-pole

10 x 38	500 V~	2
---------	--------	---

3-pole

10 x 38	500 V~	3
---------	--------	---

3-pole + neutral


10 x 38	500 V~	4
---------	--------	---

Accessories

10	057 90	Blow-out indicator 250 V~
1	057 96	Early break N/O + N/C contact auxiliary 5 A - 250 V~ (0.5 module)
2	044 44	Sealable screw cover (4 separable poles)



Blow-out indicator



Sealable screw cover

changeover switches



Dimensions see p. 145

Conform to standard IEC 60669-1
Breaking capacity AC 22 A according to IEC 60947-3

Changeover switches

Pack	Cat.No.	Nominal rating (A)	Connection	Number of modules
10	043 82	20		1
5	043 83	20		2
10	043 85	20		1
5	043 86	20		2