

ArteorTM automatic switches



ArteorTM socket outlets



5720 53









AR777AMGN



Support frames and plates selection chart (p. 90 to 91)

Mechanisms supplied with White or Magnesium square cover plates To be equipped with support frames (p. 84) and plates (p. 85 to 89)

		(1 / 1 (1 /
Pack	Cat. No.	Automatic switches - 100/240 V√
		Movement IR detection Adjustable detection distance from 3 to 10 m Horizontal detection angle: 180° Adjustable luminosity threshold: 3 to 1000 lux Time delay adjustable from 1 s to 16 min Cycle repeated as long as movement is detected Possible remote manual control with N/C push-button Integrated self-protection against overloads and short-circuits Installation in box min. depth 40 mm recommended 2 modules 22.5 x 45 mm
	White Magnesium	With neutral, 3-wire - 1000 W
1	5720 53 5740 61	Operates: - up to 1000 W incandescent and halogen lamps - up to 500 VA ELV halogen lamps with ferromagnetic or electronic transformer, fluorescent tubes and compact fluorescent lamps
		Without neutral, 2-wire - 400 W
1	5720 52 5740 62	Operates: - up to 400 W incandescent and halogen lamps - up to 400 VA ELV halogen lamps with ferromagnetic or electronic transformer



AR777WE

Plates selection chart (p. 90 to 91)

Mechanisms supplied with White or Magnesium square cover plates To be equipped with support frames (p. 84) and plates (p. 85 to 89)

Pack	Cat. No.		Socket Outlet 240 V_{\sim}
	White	Magnesium	
10	AR777AWE	AR777AMGN	10A double autoswitched socket outlet (integrated support frame)
10	AR777WE	AR777MGN	10A double switched socket outlet (integrated support frame)
10	AR787/15AMWE	AR787/15AMMGN	15A single autoswitched socket outlet (2 module)
10	AR787AMWE	AR787AMMGN	10A single autoswitched socket outlet (2 module)
10	AR787ARMWE	AR787ARMMGN	10A single autoswitched socket round earth (2 module)
10	AR787WE	AR787MGN	10A single switched socket outlet (3 module)