

CAT. N° 0 488 44



LIGHTING MANAGEMENT-DIMMER ROOM CONTROLLER-8 OUTPUTS FOR DALI BALLASTS

Pack (number of units)	1
Volume (dm ³)	3,56
Weight (g)	597,00

Product characteristics

For controlling 4 lighting circuits

- Can be controlled for each output by a sensor and/or an individual BUS control unit
- Addressing methods using sensors and control units:
 - automatic configuration
 - custom configuration by pressing the "Learn" button on the product

Dimming - DALI ballast

- 4 outputs
- 32 ballasts maximum per output

General characteristics

Lighting Management sensors for managing several circuits - multi-circuit ceiling-mounting controllers for areas with natural light

- Ceiling-mounting or installation in Cablofil cable trays (see Legrand Cable Management catalogue)
- Connection to sensors (Cat.Nos 0 488 20/22/34 and 0 784 85/86, 5 740 46/48) by cord or RJ 45 cable or BUS/SCS cable to be fitted with RJ 45 connector Cat.No 0 488 72

Documentation



Catalogue pages & additional information

- [Selection chart \(p.660\)](#)
- [Description page \(p.667\)](#)
- [Lighting management stand-alone sensors](#)



Installation & technical data

- [LE04385AB_EN](#)



Installation instructions & related documents

- [LE03164AC](#)