

Type NM



Non Metallic Conduit

NM is a multi purpose non metallic conduit offering protection from abrasion, corrosion, sunlight, mild acids, oils and alkalis.

CONSTRUCTION: Rigid PVC spiral rib within flexible PVC wall.

APPLICATION: Used for outdoor applications such as air conditioning .

PLASTIC USED: PVC

RoHS and **WEEE** Compliant

STANDARD COLOURS: Black and Grey

WORKING TEMPERATURES: -20°C to +80°C.

CHEMICAL RESISTANCE:

Refer *Chemical Resistance Guide* on www.electriflex.com.

FITTINGS: Use non metallic fittings. Type NMCM.

Type EFN

Extra Flexible Non Metallic Conduit

Extra Flexible : Orange colour, Sizes 16mm to 63mm. Oil and sunlight resistant.

WORKING TEMPERATURES: -20°C to +70°C

FITTINGS: Use NMCM fittings as per Non Metallic Fittings Section of catalogue

Part Number Description

NMO

NM016-B-10	16MM (12.5mm I.D.) NON MET OIL,UV RESISTANT BLACK CONDUIT 10M
NM016-B-30	16MM (12.5mm I.D.) NON MET OIL,UV RESISTANT BLACK CONDUIT 30M
NM016-G-30	16MM (12.5mm I.D.) NON MET OIL,UV RESISTANT GREY CONDUIT 30M
NM020-B-10	20MM (16mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 10M
NM020-B-30	20MM (16mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 30M
NM020-G-30	20MM (16mm I.D.) NON MET,OIL ,UV RESISTANT GREY CONDUIT 30M
NM025-B-10	25MM (21mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 10M
NM025-B-30	25MM (21mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 30M
NM025-G-30	25MM (21mm I.D.) NON MET,OIL ,UV RESISTANT GREY CONDUIT 30M
NM032-B-10	32MM (26.5mm I.D.) NON MET,OIL ,UV RESISTANT BACK CONDUIT 10M
NM032-B-30	32MM (26.5mm I.D.) NON MET,OIL ,UV RESISTANT BACK CONDUIT 30M
NM032-G-30	32MM (26.5mm I.D.) NON MET,OIL ,UV RESISTANT GREY CONDUIT 30M
NM040-B-10	40MM (35mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 10M
NM040-B-30	40MM (35mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 30M
NM040-G-30	40MM (35mm I.D.) NON MET,OIL ,UV RESISTANT GREY CONDUIT 30M
NM050-B-15	50MM (40.5mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 15M
NM050-G-15	50MM (40.5mm I.D.) NON MET,OIL ,UV RESISTANT GREY CONDUIT 15M
NM063-B-15	63MM (51.5mm I.D.) NON MET,OIL ,UV RESISTANT BLACK CONDUIT 15M
NM063-G-15	63MM (51.5mm I.D.) NON MET,OIL ,UV RESISTANT GREY CONDUIT 15M

EFNM

EFNM016-O-10	16MM (12.5mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 10M
EFNM016-O-30	16MM (12.5mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 30M
EFNM020-O-10	20MM (16mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 10M
EFNM020-O-30	20MM (16mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 30M
EFNM025-O-10	25MM (21mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 10M
EFNM025-O-30	25MM (21mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 30M
EFNM032-O-10	32MM (26.5mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 10M
EFNM032-O-30	32MM (26.5mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 30M
EFNM040-O-10	40MM (35mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 10M
EFNM040-O-30	40MM (35mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 30M
EFNM050-O-15	50MM (40.5mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 15M
EFNM063-O-15	63MM (51.5mm I.D.) NON MET XTRA FLEX OIL UV RES. ORG CONDUIT 15M