

Type NM2



Liquidtight Flexible Non Metallic Conduit

NM2 is extra flexible liquidtight non metallic conduit which cuts and installs easily and quickly. Ideal for wiring protection in small tight areas and tight bends. Thin flexible PVC skin allows greater movement for many applications. NM2 is self extinguishing, oil and acid resistant.

CONSTRUCTION: Co extruded from both flexible and rigid PVC with rigid spiral PVC reinforcement embedded within wall of tubing.

APPLICATION: Can be used for wiring harnesses, laboratory equipment and fiber optics.

PLASTIC USED: PVC

RoHS and WEEE Compliant

STANDARD COLOURS: Black

WORKING TEMPERATURES: -20°C to +70°C.

CHEMICAL RESISTANCE:

Refer Chemical Resistance Guide on www.electriflex.com.

FITTINGS: Use non metallic liquidtight fittings.

Part Number	Description
NM2016-B-30	16MM (12.5mm I.D.) L/TIGHT PVC OIL,ACID RESISTANT BLACK 30M
NM2020-B-30	20MM (16mm I.D.) L/TIGHT PVC OIL ,ACID RESISTANT BLACK 30M
NM2025-B-30	25MM (21mm I.D.) L/TIGHT PVC OIL ,ACID RESISTANT BLACK 30M
NM2032-B-30	32MM (26.5mm I.D.) L/TIGHT PVC OIL ,ACID RESISTANT BACK 30M
NM2040-B-30	40MM (35mm I.D.) L/TIGHT PVC OIL ,ACID RESISTANT BLACK 30M
NM2050-B-15	50MM (40.5mm I.D.) L/TIGHT PVC OIL ,ACID RESISTANT BLACK 15M
NM2063-B-15	63MM (51.5mm I.D.) L/TIGHT PVC OIL ,ACID RESISTANT BLACK 15M