

- Connector - Solid Brass
- Screws - Anodised flat head
- Temperature Rating: up to 90°C
- 12 Pole / 2 Way
- Flexible



Code	Description	MOQ
FCN-16110-B	3 amp 4mm ² - Black	10
FCN-16110-N	3 amp 4mm ² - Natural	10
FCN-16120-B	5 amp 6mm ² - Black	10
FCN-16120-N	5 amp 6mm ² - Natural	10
FCN-16125-B	10 amp 10mm ² - Black	10
FCN-16125-N	10 amp 10mm ² - Natural	10
FCN-16130-B	15 amp 12mm ² - Black	10
FCN-16130-N	15 amp 12mm ² - Natural	10
FCN-16140-B	30 amp 16mm ² - Black	10
FCN-16140-N	30 amp 16mm ² - Natural	10
FCN-16150-B	60 amp 25mm ² - Black	10
FCN-16150-N	60 amp 25mm ² - Natural	10

DIMENSIONS (mm)

Code	Amps	Length	Height	Width	Cable Entry	Mount Spacing (A)
FCN-16110	3	92	12	16	3.0	8
FCN-16120	5	103	14	19	3.5	9
FCN-16125	10	125	17	21	3.8	11.3
FCN-16130	15	130	18	22	4.2	10.9
FCN-16140	30	172	20	25	5.5	14.7
FCN-16150	60	185	26	30	6.4	16.1

