

Ventilation



- Flame retardant ABS colour RAL7035
- Available in 6 sizes from 30m³/h to 850m³/h
- 230V 50/60Hz power supply
- IP54
- Operating temperature -10 to +70°C
- Clip on mounting
- Terminal connection (except PFT1000 and PTF1500)
- Thermal overcurrent protection on larger sizes

Filter Fans (air in)

Order Code	Air Flow (m³/h)	Panel Cutout (mm)	Noise (dB(A))	Power Consumption (W)	Current (A)	Wt (kg)
17PTF1000	30	92 x 92	28	14	0.08	0.40
17PTF1500	100	125 x 125	42	26	0.14	0.68
17PTF2500	115	223 x 223	42	26	0.14	1.18
17PTF3500	240	223 x 223	52	37	0.23	1.60
17PTF4500	650	223 x 223	60	66	0.35	2.84
17PTF5000	850	291 x 291	65	110	0.65	4.12



17PTF1000



17PTF3500



17PTF4500



17PFI1500



17PFF5500



Filters (air out)

Order Code	Dimensions (mm)	Weight (kg)
17PFI1000	110 x 110 x 20.5	0.10
17PFI1500	160 x 160 x 31	0.18
17PFI2500	260 x 260 x 31	0.48
17PFI3000	325 x 325 x 31	0.70

Spare Filter Mats

Order Code	Dimensions (mm)
17PFM1000	Pack of 10 to suit 110 x 110 filter
17PFM1500	Pack of 10 to suit 160 x 160 filter
17PFM2500	Pack of 10 to suit 260 x 260 filter
17PFM3000	Pack of 10 to suit 325 x 325 filter

Roof Fans (air out)

Order Code	Air Flow (m³/h)	Panel Cutout (mm)	Noise (dB(A))	Power Consumption (W)	Current (A)	Wt (kg)
17PFF5500	560	180 x 180	62	58	0.26	3.16
17PFF6000	970	180 x 180	72	85	0.38	3.74