

Socket Outlets

The ML2000 range of socket outlets are based on the Clipsal 2000 range of socket outlets. When installing a group of socket outlets ideally one ML2000 multi-gang plate will be used with the remaining options being standard Clipsal Socket Outlets. The one ML2000 socket outlet plate will incorporate the amber Power Available Neon, Circuit Identification, and protection classification markings for the group of socket outlets.

Features

- Single or twin outlet.
- Optional Clipsal 30P-ID circuit identification.

Socket Outlets –
connected to RCD Protected Supply

- 10 or 15A.
- Single pole switched outlets.
- Marked “RCD PROTECTED”.
- Amber power available indicator.

Socket Outlets –
connected to an isolated protected supply

- 10A.
- Double pole switched outlets.
- Marked “ISOLATING TRANSFORMER PROTECTED”.

**Not all variations are available. Refer to catalogue number listing for exact options.*

Vertical

Catalogue No.	Description
ML2015V	Single gang power outlet, vertical, power neon, RCD label, 250V, 10A
ML2015VI	Single gang power outlet, vertical, power neon, RCD label, circuit identification, 250V, 10A
ML2015/15VI	Single gang power outlet, vertical, power neon, RCD label, circuit identification, 250V, 15A
ML2015VD	Single gang double pole power outlet, vertical, Isolated label, 250V, 10A
ML2015VDI	Single gang double pole power outlet, vertical, Isolated label, circuit identification, 250V, 10A
ML2025V	Double gang power outlet, vertical, power neon, RCD label, 250V, 10A
ML2025VI	Double gang power outlet, vertical, power neon, RCD label, circuit identification, 250V, 10A



ML2015V



ML2015VI



ML2015/15VI



ML2015VD



ML2015VDI



ML2025V



ML2025VI

STANDARD COLOURS

- ☐ White (WE)
- ☐ Red (RD)
- ☐ Dark Blue (DB)

Socket Outlets

Horizontal

Catalogue No.	Description
ML2015	Single gang power outlet, horizontal, power neon, RCD label, 250V, 10A
ML2015I	Single gang power outlet, horizontal, power neon, RCD label, circuit identification, 250V, 10A
ML2015/15I	Single gang power outlet, horizontal, power neon, RCD label, circuit identification, 250V, 15A
ML2015D	Single gang double pole power outlet, horizontal, power neon, Isolated label, 250V, 10A
ML2025	Double gang power outlet, horizontal, power neon, RCD label, 250V, 10A
ML2025I	Double gang power outlet, horizontal, power neon, RCD label, circuit identification, 250V, 10A

Specifications

General	Description
Operational Voltage	250V a.c. 50Hz
Max. Load	10 or 15A
Dimensions	116 x 76mm
Complies with Australian Standard	AS/NZS 3112
Approval No.	S/1/2025 series S/1/2015 series



ML2015



ML2015/15I



ML2025



ML2015I



ML2015D



ML2025I

STANDARD COLOURS

- ☐ White (WE)
- ☐ Red (RD)
- ☐ Dark Blue (DB)