


The Noremak range of nylon & un-insulated bootlace ferrules feature:

- Precise terminations for applications of where fine stranded multi core cable is used
- Reduces the possibility of short circuiting
- Colour coded for easier identification
- Temperature rating for insulated and non-insulated is +105° C
- Non-insulated range of bootlace ferrules are electro grade copper with electro tinned plated for high conductivity


NYLON INSULATED BOOTLACE FERRULES

Part Number	Description	Colour	Pack qty	Part Number	Description	Colour	Pack qty
 PBL0.34	0.34mm ² pink bootlace ferrules	Pink	100	PBL600	6.0mm ² green bootlace ferrules	Green	50
PBL050	0.50mm ² white bootlace ferrules	White	100	PBL600/500	6.0mm ² green bootlace ferrules (500pk)	Green	500
PBL050/500	0.50mm ² white bootlace ferrules (500pk)		500	PBL600-18	6.0mm ² x 18mm green bootlace ferrules		50
PBL075	0.75mm ² blue bootlace ferrules	Blue	100	PBL1000-18	10.0mm ² x 18mm brown bootlace ferrules	Brown	50
PBL075/500	0.75mm ² blue bootlace ferrules (500pk)		500	PBL1000	10.0mm ² brown bootlace ferrules		50
PBL100	1.0mm ² red bootlace ferrules	Red	100	PBL1600	16.0mm ² ivory bootlace ferrules	Ivory	50
PBL100/500	1.0mm ² red bootlace ferrules (500pk)		500	PBL1600-18	16.0mm ² x 18mm ivory bootlace ferrules		50
PBL150	1.5mm ² black bootlace ferrules	Black	100	PBL2500	25mm ² black bootlace ferrules	Black	10
PBL150/500	1.5mm ² black bootlace ferrules (500pk)		500	PBL2500-22	25mm ² x 22mm black bootlace ferrules		10
PBL150-18	1.5mm ² x 18mm black bootlace ferrules	Grey	100	PBL3500	35.0mm ² red bootlace ferrules	Red	10
PBL250	2.5mm ² grey bootlace ferrules		100	PBL3500-25	35.0mm ² x 25mm red bootlace ferrules		10
PBL250/500	2.5mm ² grey bootlace ferrules (500pk)	Grey	500	PBL5000	50.0mm ² blue bootlace ferrules	Blue	10
PBLP250-12/500	2.5mm ² x 12mm grey bootlace ferrules (500pk)		500	PBL7000	70.0mm ² yellow bootlace ferrules		5
PBL250-18	2.5mm ² x 18mm grey bootlace ferrules	Orange	100	PBL9500	95.0mm ² red bootlace ferrules	Red	5
PBL400	4.0mm ² orange bootlace ferrules		100	PBL12000	120.0mm ² blue bootlace ferrules		5
PBL400/500	4.0mm ² orange bootlace ferrules (500pk)	Orange	500				
PBL400-18	4.0mm ² x 18mm orange bootlace ferrules		100				

NYLON INSULATED TWIN BOOTLACE FERRULES


Part Number	Description	Colour	Pack qty	Part Number	Description	Colour	Pack qty
 PBLD075	Twin blue 2 x 0.75mm ² bootlace ferrules	Blue	100	PBLD025	Twin grey 2 x 2.5mm ² bootlace ferrules	Grey	100
PBLD010	Twin red 2 x 1.0mm ² bootlace ferrules	Red	100	PBLD040	Twin orange 2 x 4.0mm ² bootlace ferrules	Orange	50
PBLD015	Twin black 2 x 1.5mm ² bootlace ferrules	Black	100	PBLD060	Twin green 2 x 6.0mm ² bootlace ferrules	Green	25

UN-INSULATED BOOTLACE FERRULES

Part Number	Description	Pack qty	Part Number	Description	Pack qty
 PBLU050	Un-insulated 0.50mm ² bootlace ferrules	100	PBLU2500	Un-insulated 25.0mm ² bootlace ferrules	10
PBLU075	Un-insulated 0.75mm ² bootlace ferrules		PBLU3500	Un-insulated 35.0mm ² bootlace ferrules	
PBLU100	Un-insulated 1.0mm ² bootlace ferrules		PBLU5000	Un-insulated 50.0mm ² bootlace ferrules	
PBLU150	Un-insulated 1.5mm ² bootlace ferrules		50	PBLU7000	Un-insulated 70.0mm ² bootlace ferrules
PBLU025	Un-insulated 2.5mm ² bootlace ferrules			PBLU9500	Un-insulated 95.0mm ² bootlace ferrules
PBLU400	Un-insulated 4.0mm ² bootlace ferrules			PBLU1200	Un-insulated 120.0mm ² bootlace ferrules

The Noremak range meets all the conformant standards.

CLOSED END CONNECTORS

Part Number	Description	Pack qty
 TCEC-1	Closed end connector 0.5 - 1.5mm ²	50
TCEC-2	Closed end connector 1.5 - 2.5mm ²	25
TCEC-5	Closed end connector 4.0 - 6.0mm ²	



TERMINAL SERIES

Terminal colour	RD	BL	YW
Conductor range (mm ²)	0.5-1.5	1.5-2.5	4.0-6.0
Strip length for terminals (mm)	4-5	5-6	6-7
Strip length for inline splice (mm)	7-8	7-8	7-8

The cable as a guide should protrude 1mm out of the front of the terminal.

The Noremak range of pre-insulated terminals feature:

- Double Grip to ensure stronger pull out force
- Three piece manufacturing process
- Colour coded vinyl insulated for easier identification of cable sizes
- Temperature rating on vinyl is +75°C, our Nylon range is rated at +105°C

DOUBLE GRIP RING TERMINALS

Part Number	Stud (mm)	RD	Pack qty	Part Number	Stud (mm)	BL	Pack qty	Part Number	Stud (mm)	YW	Pack qty
TRRDD-3	3.2	RD	100	TRBUD-4	4.3	BL	100	TRYED-4	4.3	YW	50
TRRDD-4	4.3			TRBUD-5	5.3			TRYED-5	5.3		
TRRDR-5	5.3			TRBUD-6	6.4			TRYED-6	6.4		
TRRDD-6	6.4			TRBUD-8	8.4			TRYED-8	8.4		
TRRDD-8	8.4			TRBUD-10	10.5			TRYED-10	10.0		
TRRDD-10	10.5			TRBUD-12	13.0			TRYED-12	12.0		

DOUBLE GRIP SPADES/FORKS

Part Number	Stud (mm)	RD	Pack qty	Part Number	Stud (mm)	BL	Pack qty	Part Number	Stud (mm)	YW	Pack qty
TFRDD-3	3.2	RD	100	TFBUD-3	3.2	BL	100	TFYED-3	3.7	YW	50
TFRDD-3.5	3.7			TFBUD-3.5	3.7			TFYED-4	4.3		
TFRDD-4	4.3			TFBUD-4	4.3			TFYED-5CS	5.3		
TFRDD-5	5.3			TFBUD-5	5.3			TFYED-6	6.4		
TFRDD-6	6.4										

DOUBLE GRIP PINS

Part Number	Pin (mm)	RD	Pack qty	Part Number	Pin (mm)	BL	Pack qty	Part Number	Pin (mm)	YW	Pack qty
TPRDD-9	9	RD	50	TPBUD-9	9	BL	50	TPYED-9	14	YW	25

DOUBLE GRIP BUTT SPLICES

Part Number	Length (mm)	RD	Pack qty	Part Number	Length (mm)	BL	Pack qty	Part Number	Length (mm)	YW	Pack qty
TJRDD	26	RD	50	TJBUD	26	BL	50	TJYED	27	YW	25

HEAT SHRINK DOUBLE GRIP BUTT SPLICES - WATERPROOF CONNECTIONS

Part Number	Length (mm)	RD	Pack qty	Part Number	Length (mm)	BL	Pack qty	Part Number	Length (mm)	YW	Pack qty
TJRDD-W	38	RD	25	TJBUD-W	35	BL	25	TJYED-W	41	YW	25

DOUBLE GRIP FLAT BLADES

Part Number	Pin (mm)	RD	Pack qty	Part Number	Pin (mm)	BL	Pack qty	Part Number	Pin (mm)	YW	Pack qty
TBRDD-S	20	RD	50	TBBUD-S	20	BL	50	TBYED-S	24	YW	25
TBRDD-L	29			TBBUD-L	29			TBYED-L	32		

DOUBLE GRIP LIP BLADES

Part Number	Blade (mm)	RD	Pack qty	Part Number	Blade (mm)	BL	Pack qty	Part Number	Blade (mm)	YW	Pack qty
TBLRDD-S	3	RD	50	TBLBUD-S	3	BL	50	TBLYED-S	3	YW	25
TBLRDD-L	5			TBLBUD-L	5			TBLYED-L	5		

DOUBLE GRIP QC DISCONNECTS MALE FUNNEL ENTRY

Part Number	Tab (mm)	RD	Pack qty	Part Number	Tab (mm)	BL	Pack qty	Part Number	Tab (mm)	YW	Pack qty
TQMRDD-6	6.4x0.8	RD	50	TQMBUD-6	6.4x0.8	BL	50	TQMYED-6	6.4x0.8	YW	25

DOUBLE GRIP QC FULLY INSULATED

Part Number	Tab (mm)	RD	Pack qty
TQFRDD4-5	4.8x0.5	RD	100
TQFRDD4-8	4.8x0.8		

FEMALE FUNNEL ENTRY

Part Number	Tab (mm)	BL	Pack qty
TQFBUD4-5	4.8x0.5	BL	100
TQFBUD4-8	4.8x0.8		

DOUBLE GRIP NYLON 105 °C FULLY INSULATED FEMALE FUNNEL ENTRY

Part Number	Tab (mm)	RD	Pack qty	Part Number	Tab (mm)	BL	Pack qty	Part Number	Tab (mm)	YW	Pack qty
TQFRDD-N	6.4x0.8	RD	100	TQFBUD-N	6.4x0.8	BL	100	TQFYED-N	6.4x0.8	YW	50

DOUBLE GRIP QC FEMALE FUNNEL ENTRY

Part Number	Tab (mm)	RD	Pack qty	Part Number	Tab (mm)	BL	Pack qty	Part Number	Tab (mm)	YW	Pack qty
TQFRDD2-5	2.8x0.5	RD	100	TQFBUD2-5	2.8x0.5	BL	100	TQFYED6-8	6.4x0.8	YW	25
TQFRDD2-8	2.8x0.8			TQFBUD2-8	2.8x0.8						
TQFRDD4-5	4.8x0.5			TQFBUD4-5	4.8x0.5						
TQFRDD4-8	4.8x0.8			TQFBUD4-8	4.8x0.8						
TQFRDD6-8	6.4x0.8			TQFBUD6-8	6.4x0.8						

DOUBLE GRIP QC PIGGY BACKS FUNNEL ENTRY

Part Number	Tab (mm)	RD	Pack qty	Part Number	Tab (mm)	BL	Pack qty	Part Number	Tab (mm)	YW	Pack qty
TQPRDD6-8	6.4x0.8	RD	50	TQPBD6-8	6.4x0.8	BL	50	TQPYED6-8	6.4x0.8	YW	25

NYLON FLAG QC FEMALE DISCONNECTS 105 °C FULLY INSULATED FUNNEL ENTRY

Part Number	Tab (mm)	RD	Pack qty	Part Number	Tab (mm)	BL	Pack qty
TQARDD6-9	6.4x0.8	RD	25	TQABUD6-9	6.4x0.8	BL	25

DOUBLE GRIP FEMALE BULLETS FUNNEL ENTRY

Part Number	Bullet (dia mm)	RD	Pack qty	Part Number	Bullet (dia mm)	BL	Pack qty	Part Number	Bullet (dia mm)	YW	Pack qty
TQFRDD1-4	4	RD	50	TQFBUD1-4	4	BL	50	TQFYED1-4	5	YW	25

DOUBLE GRIP MALE BULLETS FUNNEL ENTRY

Part Number	Bullet (dia mm)	RD	Pack qty	Part Number	Bullet (dia mm)	BL	Pack qty	Part Number	Bullet (dia mm)	YW	Pack qty
TQMRDD1-4	4	RD	50	TQMRDD1-4	4	BL	50	TQMYED1-4	5	YW	25