

# POWERLEX® PVC Multicore Flexible OD Cords

## CU POWERLEX-OD 2X 0.75+E GY V90

### Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries  
Phone: 1300 CABLES  
olex.customerservice@nexans.com

Nexans ref.: EAHR02A1003GYAA

GTIN: 9319215049959

3X0.75mm<sup>2</sup> (2C+E) Powerlex OD Grey

### DESCRIPTION

250/440V V-90 insulated and sheathed ordinary duty flexible cord to AS/NZS 3191 and AS/NZS 60227 and to PVC Best Practice Guidelines.

- 250/440V
- V-90 insulated and sheathed ordinary duty flexible cord to AS/NZS 3191 and AS/NZS 60227.

**Note:** V-90HT is available on request subject to minimum production runs.



### STANDARDS

**National** AS/NZS 3191; AS/NZS 60227



Rated Voltage U<sub>0</sub>/U (Um)  
**250/440 V**

All drawings, designs, specifications, plans and particulars of weights, size and dimensions contained in the technical or commercial documentation of Nexans is indicative only and shall not be binding on Nexans or be treated as constituting a representation on the part of Nexans.

Generated 23/12/20    [www.olex.com.au](http://www.olex.com.au)    Page 1 / 2

# POWERLEX® PVC Multicore Flexible OD Cords

## CU POWERLEX-OD 2X 0.75+E GY V90

### Contact

OLEX CUSTOMER SERVICE - Purchase orders, invoices, general enquiries  
Phone: 1300 CABLES  
olex.customerservice@nexans.com

## CHARACTERISTICS

### Construction characteristics

Conductor material	Copper
With Green/Yellow core	Yes
Outer sheath	PVC
Colour	Grey
Insulation colour	Brown, light blue, Green/yellow
Type of conductor	Copper
Insulation	V-90

### Dimensional characteristics

Maximum diameter of wires	0.21 mm
Conductor cross-section	0.75 mm <sup>2</sup>
Number of earth cores	1
Number of cores	3
Nominal overall diameter	6.6 mm
Approximate weight	7.0 kg/100m
Cable length	100 m

### Electrical characteristics

Inductive reactance at 50Hz	0.122 Ohm/km
Insulation resistance at 20°C	17.0 MOhm.km
Max. DC resistance of the conductor at 20°C	26 Ohm/km
A.C. Conductor resist. 50Hz and at 90 °C	31.6 Ohm/km
Rated Voltage U <sub>o</sub> /U (U <sub>m</sub> )	250/440 V