


# PRODUCT DATASHEET

## SPC.T CL 25 W 230 V E14

**SPECIAL T | Incandescent lamps, tubular shape**



## TECHNICAL DATA

### Electrical data

Rated wattage	25.00 W
Nominal wattage	25.00 W
Power factor $\lambda$	1.00


### Photometrical data

Nominal luminous flux	160 lm
Rated luminous flux	160 lm
Rated color temperature	2700 K
Color temperature	2700 K
Luminous flux	160 lm
Color rendering index Ra	100
Color rendering index Ra	100

### Light technical data

Starting time	0.0 s
Warm-up time (60 %)	0.00 s

### Dimensions & weight



Diameter	26.0 mm
Overall length	55.0 mm
Outer bulb	T26
Light center length (LCL)	45.0 mm
Length with base excl. base pins/connection	57.00 mm
Length	55.0 mm

### Lifespan

Nominal lamp life time	1000 h
------------------------	--------

<b>Rated lamp life time</b>	1000 h
-----------------------------	--------

## Additional product data

<b>Base (standard designation)</b>	E14
<b>Mercury content</b>	0.0 mg
<b>Mercury-free</b>	Yes

## Capabilities

<b>Dimmable</b>	Yes
-----------------	-----

## Certificates &amp; standards

<b>Energy efficiency class</b>	E
<b>Energy consumption</b>	25 kWh/1000h

## Country-specific categorizations

<b>ILCOS</b>	IBT/C-25-230-E14-26
--------------	---------------------

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4050300309637	Folding carton box 1	61 mm x 27 mm x 27 mm	12.00 g	0.04 dm <sup>3</sup>
4050300819822	Bundle 10	73 mm x 61 mm x 117 mm	120.00 g	0.52 dm <sup>3</sup>
4050300976716	Shipping carton box 100	285 mm x 140 mm x 150 mm	1301.00 g	5.99 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.