

BWP/T

A versatile range of weatherproof fluorescent luminaires for adverse conditions and exposed environments.



Specification

- Self extinguishing and UV stabilised polycarbonate body in a neutral light grey colour
- Clear prismatic polycarbonate lens resists impact and abuse
- T8 4000K lamps included
- Supplied with robust and lockable stainless steel clips fitted to the body, rated IK08
- 20mm cable entry with PG8.5 gland and optional knock-out at the opposite end
- Clip-in modular gear tray with safety lanyards for easy installation and maintenance
- Durable polyurethane foam seal ensures the IP65 weather protection; tested to 40°C ambient
- V90T internal wiring and 3-way terminal block with fused active
- Designed for horizontal surface mount installation and supplied with stainless steel mounting clips for easy installation without compromising the IP integrity



Quick Spec

Pierlite BWP/T polycarbonate IP65 weatherproof housing with stainless steel clips and modular gear tray. Stainless steel mounting clips.

Design Application

Exposed applications around waterfront areas, car parks, industrial and construction sites and for general security.

Product Codes

Code	Version	Dim (mm)	Mass (kg)
BWP/T118H	1 x 18W T8 HPF	670 x 98 x 104	2.5
BWP/T218H	2 x 18W T8 HPF	670 x 152 x 104	3.1
BWP/T136H	1 x 36W T8 HPF	1300 x 98 x 104	3.1
BWP/T236H	2 x 36W T8 HPF	1300 x 152 x 104	3.5
BWP/T118EL	1 x 18W T8 EL	670 x 98 x 104	2.3
BWP/T218EL	2 x 18W T8 EL	670 x 152 x 104	2.9
BWP/T136EL	1 x 36W T8 EL	1300 x 98 x 104	2.9
BWP/T236EL	2 x 36W T8 EL	1300 x 152 x 104	3.3

Performance

