

## Litelux Colour Select Downlight Gen4

### DLP53/4/65FWG4

- Generation 4 with remote driver enabling installation into the lowest of ceiling cavities.
- IC-4 compliant - Safe against building thermal materials and insulation.
- Select colour temperature from 3000K, 4000K, or 6500K with dip switch conveniently located on driver.



## COLOUR SELECT

### Performance

Lamp Power	7.8W
Exit Lumen	870lm
Efficacy	111lm/W
CCT	4000K, 3000K, 6500K
CRI	80
Operating Temperature	0 to 40
MacAdam Steps	6SDCM
Ingress Protection Rating	IP65
Impact Rating	IK02
Beam Distribution	Symmetric
Warranty	3 Years
Lifetime	50,000hrs (L70/B10) @ 40°C
Turtle Friendly	No


### Physical

Dimensions	L115 x W115 x H33 mm
Cutout Diameter	90mm
Diffuser	Opal
Luminaire Colour	White
Weight	0.26kg
Driver Location	Remote
Minimum Recess Depth	40
Finish	White
Installation	Recessed

### Electrical

Dimming	Phase
Voltage	240V
Line Voltage Frequency	50Hz
Inrush Current	1.3A
Inrush Current Duration	132µs
Line Current	3.5A
Surge protection	Yes
Electrical Rating	Class II

### Line Drawings



### Product Images



