



PIPEMAKERS AUSTRALIA PTY LTD
A.C.N 061 712 365 A.B.N 76 061 712 365

UPVC COUPLING DATA SHEET

1.0 General

- 1.1 Pipemakers Australia Couplings are manufactured in solid wall or sandwich construction.
- 1.2 Sizes range from DN 20 to DN 200. Sizes above DN 150 are to be agreed between Pipemakers Australia and the purchaser.
- 1.3 All Couplings are manufactured to AS/NZS 2053.2
- 1.4 UPVC Couplings are supplied with suitable packaging.

2.0 Raw Material

- 2.1 PVC resin and additives suitable to meet the requirements of AS/NZS 2053.2 are used.
- 2.2 Couplings are White OR Orange in colour, as per AS/NZS 2053.

3.0 Dimensions

All dimensions are in mm.

COUPLINGS (Orange/White)

Nominal Outside Diameter	Socket Type FF – female/female, FM – female/male, MM – male/male
20	FF
25	FF
32	FF
40	FF
50	FF
63	FF
80	FF
100	FF
125	FF
150	FF
200	FF

SLIP REPAIR COUPLINGS (Orange/White)

Nominal Outside Diameter	No Socket
50	Without socket
63	Without socket
80	Without socket
100	Without socket
125	Without socket
150	Without socket
200	Without socket