

Gap Seal

Paintable Acrylic Gap Sealant



RamsetTM

Sealants



Features & Benefits

- Resists cracking - flexible
- Paintable
- User Friendly – clean up with water
- User Friendly – low odour
- Easy to use – sag resistant
- Low VOC

Description

Gap Seal paintable acrylic sealant is flexible to resist cracking when used to seal gaps and cracks prior to painting. Gap Seal provides a neat and tidy finish around architraves, skirtings, chair and picture rails and is paintable with acrylic and oil based surface coatings.

Typical Properties

Appearance	White, non-sag smooth thixotropic paste
Chemical Type	Water-based Acrylic
Service Temperature	-10°C to + 80°C
Application Temperature	+5°C to + 35°C
Tool Working Time	15 minutes at 20°C
Max. Joint Movement	± 5%
Max. Joint Width	50mm
Elongation at Break ASTM D412	400%
Cure Rate	2mm per 24 hour period
Cure Hardness	Shore D 50
Skinning Time	30 minutes @ 20°C
Paintable	Acrylic and Vinyl paints – 30 minutes at 20°C Oil based paints – 24 hours
Substrates	Plasterboard, MDF, Plywood, Ceramic Tiles, Laminated Plastics, Timber, Fibre cement, Concrete & Brick

Trades & Applications

	Ceiling & Partitioning	Shop Fitter	Painter
Sealing Partition Joints	✓		✓
Sealing Joinery		✓	✓

Related Products

Caulking Gun

Installation

1. Ensure surfaces are clean and dry
2. For best results mask around gap to be filled
3. Dispense Gap Seal sealant into gap or joint with continuous trigger pressure
4. Tool sealant to create a neat finish
5. Remove masking tape before Gap Seal Skins
6. Clean up Gap Seal with a damp cloth before it dries.

Refer to Technical Data Sheet and MSDS available from www.ramset.com.au, for precautions and further detailed installation instructions

Gap Seal

Part No.	Colour	Volume	Order Qty
GPSLWHG450	White	300mL Cartridge	20

Flexibility	Low	Low VOC	Yes
Water Resistance	Low	Paintable	Yes
Water Immersion	No	Water Clean Up	Yes
Heat Resistant	No	Exterior Use	No
Fire Rated	No	UV Resistant	No