## Catalogue No: RL24IC

## REMLIVE ISOLATOR CHECK 24-1000V AC 26-1000V DC

Signalling Devices > Sight Indication > Beacons > RemLive Indication > Remlive Isolation Indicator - Comes with All Parts Required





REMLIVE Positive Isolation/Live Line Indicator 24-1000V AC 26-1000V DC (Monitoring Unit + Display + RJ45 Cable)

- Super bright display providing operators a quick and easy method of proof of isolation in lock out-tag out procedures
- Fully IP 66 certified ensuring your switchboard maintains its overall ingress protection rating
- Using V0 rated plastics with CE, uL and CSA certifications providing local and international certification compliance
- Applicable to a broad range of voltages from 24-1000V DC and 24-690V AC with only one unit
- Low voltage to the door (3.8V DC) ensuring safety for operators
- Simple 30.5mm footprint makes installation and maintanence a breeze - simply knock out the hole, install the indicator and tighten the lock nut
- Low current consumption (max 50 mA) with resettable fuse link

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS		
Ue, Rated Operational Voltage, AC, min		24 V AC
Ue, Rated Operational Voltage, AC, max		1000 V AC
Ue, Rated Operational Voltage, DC, min		26 V DC
Ue, Rated Operational Voltage, DC, max		1000 V DC
Input Frequency, Nom		50 / 60 Hz
Input Current, Max (rms)		50 mA, max rms
Material, Body / Housing		PC (Polycarbonate) material
		IP66
Mounting		DIN-35 Rail Mount
Standards Compliance		IEC 60204-1 / EN 60204-1 (Safety Stop Categories)
REFERENCES		
IECEx Certificate	=	
Supplier Declaration of Conformity:	-	
Installation Guide:	Installation Guidet	
User Manual:	Data Sheet	
Manufacturer Datasheet:	-	
Manufacturer Catalogue & Product Selection:	-	

