

Rittal – The System.

Faster – better – everywhere.

TopTherm fan-and- filter units – SK 3240.100

Date : Sep 20, 2022

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TopTherm fan-and-filter units – SK 3240.100

created: 20.09.2022 on www.rittal.com/com-en



Product description	
Protection category IP to IEC 60 529:	IP 54 with standard filter and additional fine filter mat: IP 55 with standard filter and hose-proof hood: IP 56
Protection category NEMA:	Type 12 with standard filter and additional fine filter mat: Type 12 with standard filter and hose-proof hood: Type 3, 3R, 4, 4X
Supply includes:	Complete unit ready to install, including filter mat
Note:	With the fan-and-filter unit 3237.XXX, electrical connection is made via two single wires (length approx. 300 mm) on the unit, for all other fan-and-filter units, a screwless spring terminal is used
Product description	
Air throughput (unimpeded air flow):	At 50 Hz: 180 m³/h At 60 Hz: 160 m³/h
Air throughput with outlet filter including standard filter mat (quantity x order number, output 50/60 Hz):	1 x 3240200: 138/121 m³/h 2 x 3240200: 165/140 m³/h 1 x 3243200: 165/140 m³/h
Rated operating voltage:	230 V, 1~, 50 Hz/60 Hz
Dimensions:	Width: 255 mm Height: 255 mm
Required mounting	Width: 224 mm

cut-out:	Height: 224 mm
Build depth:	25 mm
Installation depth:	107 mm
Temperature range:	Bearing: -30 °C...+70 °C Operation (environment): -30 °C...+55 °C
Power consumption P_{el}:	At 50 Hz: 35 W At 60 Hz: 34 W
Rated current max.:	At 50 Hz: 0.21 A At 60 Hz: 0.19 A
Miniature circuit-breaker/fuse:	2 A
Service life at 50 Hz:	72000 h
Service life at 60 Hz:	76000 h
Noise level:	At 50 Hz: 51 dB(A) At 60 Hz: 46 dB(A)
Colour:	RAL 7035
Fan:	Diagonal, shaded pole motor
eCl@ss 8.0/8.1:	27180716
Packs of:	1 pc(s).
Weight/pack:	2.26 kg
EAN:	4028177651937
Customs tariff number:	84145915
ETIM 7.0:	EC000320
ETIM 6.0:	EC000320
eCl@ss 8.0/8.1:	27180716
eCl@ss 6.0/6.1:	27180716
Product description:	SK fan and filter units TopTherm, 180/160 m³/h, 230 V, 1~, 50/60 Hz, WHD: 255 x 255 x 25 mm

Approvals

Approvals:	Approval overview CCC exception letter CSA UL + C-UL - FTTA UR + C-UR
-------------------	---

Certificates:	EAC
----------------------	-----

Declarations:	Declaration of conformity
----------------------	---------------------------