

COMMERCIAL SPACE LED PANEL



SPACE LED panel, 1200x300mm, white

- Suitable for use in offices, shops, hotels, restaurants, reception areas, schools, health centres, hospitals
- LED replacement for 2 x 36W T8
- Fits into standard sizes of ceiling grid – 15mm and 24mm
- 50,000 hour average lamp life. Up to 5 times that of a standard fluorescent
- 3 wire suspension system available – can suspend panel to a length of 1.2M (RAMSUS-3W)
- Surface mounted boxes available (R1230SMKFB-01 and R1230SMKFBS-0)
- Recessed plaster board frame available (R1230RF)
- Simple to install and low/no maintenance
- C/w 1m flex and plug
- High efficacy of 93-105Lm/W
- Suitable for switching by external PIR, Microwave or Photocell



Motor Trade Association, Barton, Australia Capital Territory

30W

	Neutral White	Cool White	Daylight White
	RP30403012-01	RP30503012-01	RP30653012-01
Comparable to:	2 X 36W	2 X 36W	2 X 36W
Total Power (W):	29.6	30.3	25.6
Power Factor (PF):	0.95	0.95	0.95
Total Light Output (lm):	3,100	3,010	2,840
Efficacy (lm / cctW):	105	100	96
Lifetime (hrs):	50,000	50,000	50,000
Lux at 1m (lx):	1,060	1,040	980
Beam Angle (deg):	110	110	110
CCT (K):	4000	5000	6500
CRI:	80	80	80
IP:	20	20	20
Length (mm):	1,195	1,195	1,195
Width (mm):	295	295	295
Depth (mm):	9	9	9
Weight (kg):	2.5	2.5	2.5

40W

	Neutral White	Daylight White
	RP40403012-01	RP40653012-01
Comparable to:	2 X 36W	2 X 36W
Total Power (W):	36.7	36.7
Power Factor (PF):	0.95	0.95
Total Light Output (lm):	3,710	3,400
Efficacy (lm / cctW):	101	93
Lifetime (hrs):	50,000	50,000
Lux at 1m (lx):	1,280	1,180
Beam Angle (deg):	110	110
CCT (K):	4000	6500
CRI:	80	80
IP:	20	20
Length (mm):	1,195	1,195
Width (mm):	295	295
Depth (mm):	10	10
Weight (kg):	2.5	2.5

