

COMMERCIAL SPACE LED PANEL



SPACE LED panel, 600x1200mm, white

- Suitable for use in offices, shops, hotels, restaurants, reception areas, schools, health centres, hospitals
- LED replacement for 4 x 36W T8
- Fits into standard sizes of ceiling grid – 15mm and 24mm
- 50,000 hour average lamp life. Up to 5 times that of a standard fluorescent
- 6 wire suspension system available – can suspend panel to a length of 1.2M (RAMSUS-6W)
- Surface mounted boxes available (R60120SMKFB-01 and R60120SMKD-01)
- Simple to install and low/no maintenance
- C/w 1m flex and plug
- High efficacy of 89-101lm/W
- Suitable for switching by external PIR, Microwave or Photocell

60W

	Neutral White RP60406012-01	Daylight White RP60656012-01
Comparable to:	4X36W	4X36W
Total Power (W):	60.6	58.2
Power Factor (PF):	0.95	0.95
Total Light Output (lm):	5,380	5,850
Efficacy (lm / cctW):	89	101
Lifetime (hrs):	50,000	50,000
Lux at 1m (lx):	1,860	2,020
Beam Angle (deg):	110	110
CCT (K):	4000	6500
CRI:	80	80
IP:	20	20
Length (mm):	1,195	1,195
Width (mm):	595	595
Depth (mm):	9	9
Weight (kg):	3	3

