# STRIBE 5M IP65 LED Striplight Rolls - 7.2W p/m Available in Warm White, Day White & RGB

- 5m roll of IP65 7.2W/m flexi striplight
- Strip can be cut every 5 LED's and reconnected as required (Please refer to instruction guide on our website)
   Each roll c/w connector starter pack, which includes heat shrink, wire connectors, end caps, clips and glue
   Pack of extra connectors available to order (Single Colour: RVB5030-CONN, RGB: RVBRGB-CONN)

- Single colour strip can be used with controller
- (RVB3050-CRTL) to enable dimming
- RGB strip can be used with controller (RVBRGB-CRTL) to enable colour changing and dimming
- Single colour strip can be used with amplifier (RVB3050-AMP) to extend to lengths greater than 10m
- RGB strip can be used with amplifier (RVBRGB-AMP) to extend to lengths greater than 10m
- Choose from 60W, 100W or 200W power supply depending on length required (RVB060-PSU, RVB100-PSU, RVB200-PSU)

	5M	5M	5M
	Warm White	Cool White	RGB
	RVB0073005I65	RVB0075005165	RVB007RGB05I65
Total Power (W):	7.2 p/m	7.2 p/m	7.2 p/m
Total Light Output (lm):	350p/m	400p/m	NA
Beam Angle (deg):	120	120	120
CCT (K):	3,000	5,000	NA
CRI:	70	70	NA
Lifetime (hrs):	30,000	30,000	30,000
Length (mm):	5,000	5,000	5,000
Width (mm):	12	12	12
Height (mm):	4	4	4
Weight (kg):	2.9	2.9	2.9
IP:	65	65	65















# STRIBE 10M IP65 LED Striplight Rolls - 7.2W p/m Available in Warm White, Day White & RGB $\,$

- 10m roll of IP65 7.2W/m flexi striplight
- Strip can be cut every 5 LED's and reconnected as required (Please refer to instruction guide on our website)
- Each roll c/w connector starter pack, which includes heat shrink, wire connectors, end caps, clips and glue
- Pack of extra connectors available to order (Single Colour: RVB5030-CONN, RGB: RVBRGB-CONN)
- Single colour strip can be used with controller
- (RVB3050-CRTL) to enable dimming
   RGB strip can be used with controller (RVBRGB-CRTL) to enable colour changing and dimming
- Single colour strip can be used with amplifier (RVB3050-AMP) to extend to lengths greater than 10m
- RGB strip can be used with amplifier (RVBRGB-AMP) to extend to lengths greater than 10m
- Choose from 60W, 100W or 200W power supply depending on length required (RVB060-PSU, RVB100-PSU, RVB200-PSU)

	10M	10M	10M
	Warm White	Cool White	RGB
	RVB0073010I65	RVB0075010I65	RVB007RGB10I65
Total Power (W):	7.2 p/m	7.2 p/m	7.2 p/m
Total Light Output (lm):	350p/m	400p/m	NA
Beam Angle (deg):	120	120	120
CCT (K):	3000	5000	NA
CRI:	70	70	NA
Lifetime (hrs):	30,000	30,000	30,000
Length (mm):	10,000	10,000	10,000
Width (mm):	12	12	12
Height (mm):	4	4	4
Weight (kg):	5.6	5.6	5.6
IP:	65	65	65

















ROBUS 101

# STRIBE 5M IP65 LED Striplight Rolls - 14.4W p/m Available in Warm White, Day White & RGB

- 5m roll of IP65 14.4W/m flexi striplight
- Strip can be cut every 6 LED's and reconnected as required [Please refer to instruction guide on our website]
- Each roll c/w connector starter pack, which includes heat shrink, wire connectors, end caps, clips and glue

- Pack of extra connectors, end caps, ctips and gitte
  Pack of extra connectors available to order
  [Single Colour: RVB5030-CONN, RGB: RVBRGB-CONN]
  Single colour strip can be used with controller
  [RVB3050-CRTL] to enable dimming
  RGB strip can be used with controller [RVBRGB-CTRL]
  to enable colour changing and dimming
- Single colour strip can be used with amplifier (RVB3050-AMP) to extend to lengths greater than 10m
- RGB strip can be used with amplifier (RVBRGB-AMP) to extend to lengths greater than 10m
  Choose from 60W, 100W or 200W power supply depending on length required (RVB060-PSU, RVB100-PSU, RVB200-PSU)

	5M	5M	5M
	Warm White	Day White	RGB
	RVB0143005I65	RVB0145005I65	RVB014RGB05I65
Total Power (W):	14.4 p/m	14.4 p/m	14.4p/mr
Total Light Output (lm):	700p/m	800p/m	NA
Beam Angle (deg):	120	120	120
CCT (K):	3,000	5,000	NA
CRI:	70	75	NA
Lifetime (hrs):	30,000	30,000	30,000
Length (mm):	5,000	5,000	5,000
Width (mm):	12	12	12
Height (mm):	4	4	4
Weight (kg):	2.9	2.9	2.9
ID .	45	45	45













# STRIBE 10M IP65 LED Striplight Rolls - 14.4W p/m Available in Warm White & Day White

- 10m roll of IP65 14.4W/m flexi striplight
- Strip can be cut every 6 LED's and reconnected as required (Please refer to instruction guide on our website)
- Each roll c/w connector starter pack, which includes heat shrink, wire connectors, end caps, clips and glue
- Pack of extra connectors available to order (Single Colour: RVB5030-CONN, RGB: RVBRGB-CONN)
   Single colour strip can be used with controller (RVB3050-CRTL) to enable dimming
   RGB strip can be used with controller (RVBRGB-CTRL)
- to enable colour changing and dimming
- Single colour strip can be used with amplifier (RVB3050-AMP) to extend to lengths greater than 10m
- RGB strip can be used with amplifier (RVBRGB-AMP)
- to extend to lengths greater than 10m
   Choose from 60W, 100W or 200W power supply depending on length required (RVB060-PSU, RVB100-PSU, RVB200-PSU)

	10M	10M
	Warm White	Day White
	RVB0143010I65	RVB0145010I65
Total Power (W):	14.4p/m	14.4 p/m
Total Light Output (lm):	700 p/m	800 p/m
Beam Angle (deg):	120	120
CCT (K):	3,000	5,000
CRI:	70	75
Lifetime (hrs):	30,000	30,000
Length (mm):	10,000	10,000
Width (mm):	12	12
Height (mm):	4	4
Weight (kg):	5.6	5.6
IP:	65	65













ROBUS 103