





COOLUM PLUS S9069/TC - 12W

12 watt dimmable downlight, UGR<19, with flex and plug termination and selectable colour temperature

Application

Perfect for residential or commercial applications

Design Specifications

- 12 watt integral dimmable driver
- A versatile design supplied with flex and plug fitted for easy installation
- High efficiency SMD LED chips, multi-faceted optical system
- CRI > 80, selectable CCT 3000 / 4000 / 5700K, beam distribution 60 degree, UGR<19
- Polyamide trim and body form in white or black
- IC 4 rated



















Performance

Dimmable - YES

Dimmer Type - Trailing edge


Technical Specification

Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	сст (к)	Beam Angle (°)	Dimmable
S9069TC/WH	240	12	840/920/900	3000/4000/5700	60	YES
S9069TC/BK	240	12	680/740/720	3000/4000/5700	60	YES

Model No.	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
S9069TC/WH	WHITE	120	140	140(W) x 102(H)
S9069TC/BK	BLACK	120	140	140(W) x 102(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions







Photometric Data

Photometric Data





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

