



ECOLINE MKIII SL9732TC/DP3 - 10/50W

LED narrow diffused batten with selectable CCT and dual power

Application

Conventional linear LED batten products for commercial service spaces

Design Specifications

- 65 mm narrow steel body
- Quality white powder coat finish with robust polycarbonate diffuser
- Large terminal block, easy installation
- Easy selectable colour temperature with an inbuilt DIP switch 3000K/4000K/5700K
- High efficiency (>125lm/W at 4000K) SMD LED, CRI >80, 120° beam distribution
- Integral constant current non-dimmable LED driver with selectable power,



Performance

- Dimmable - **OPTIONAL**
- Dimmer Type - **Trailing edge, 1-10V, DALI/DSI**
- In Built Sensor - **OPTIONAL**
- Sensor Type - **MICROWAVE**

Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	SL9732/20TC/DP3	240	10/20	2370/2600/2460	3000/4000/5700	80
	SL9732/40TC/DP3	240	20/40	4600/5100/4860	3000/4000/5700	80
	SL9732/50TC/DP3	240	25/50	6100/6700/6300	3000/4000/5700	80


Beam Angle (°)	Dimmable	Dim (mm)	Body Colour	IPART	VEET
120	OPTIONAL	600(L) x 65(W) x 65(H)	WHITE	N/A	N/A
120	OPTIONAL	1135(L) x 65(W) x 65(H)	WHITE	N/A	N/A
120	OPTIONAL	1455(L) x 65(W) x 65(H)	WHITE	N/A	N/A

NOTE: lumens (lm) shown are at FULL power setting


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

Dimensions

SL9732 20



SL9732 40



THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

