



ECOLINE WIDE SL9738 TC/DP2 - 12/40W

LED WIDE diffused batten with selectable colour temperature and dual power

Application



Conventional style (wide) linear LED batten products for commercial service spaces

Design Specifications

- 110 mm WIDE steel body
- Quality white powder coat finish with robust polycarbonate diffuser
- Large terminal block, easy installation
- Easy selectable colour temperature with an inbuilt DIP switch 3000K/4000K/5700K
- High efficiency SMD LED, CRI >80, 120° beam distribution



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Multiple Wattage	Lumens (lm)	CCT (K)	CRI
	SL9738/20TC/DP2	240	12/20	2300/2500/2400	3000/4000/5700	80
	SL9738/40TC/DP2	240	24/40	4900/5300/5100	3000/4000/5700	80

Beam Angle (°)	Dimmable	Dim (mm)	Body Colour
120	NO	610(L) x 110(W) x 65(H)	WHITE
120	NO	1225(L) x 110(W) x 65(H)	WHITE

NOTE: lumens (lm) shown are at FULL power setting

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE NEW ESS106 IS SMALL IN SIZE BUT BIG ON FEATURES.



For more
information
please
scan me

