





ECOSTAR S9046TC - 9W

Dimmable 9 watt gimbal LED downlight with selectable CCT

Application

Ideal for any residential or commercial interior spaces

Design Specifications

- Durable die-cast aluminium body profile
- Stylish powder coat finish in white or plated satin nickel
- Versatile gimbal head with 30 degree tilt, IC- 4 rated
- High output LED optics, 60 Deg standard beam, CRI >
- Remote constant current trailing edge dimmable LED driver with flex and plug
- 92mm cut-out

Performance

- Dimmable YES
- Dimmer Type Trailing edge, 1-10V, DALI / DSI























Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Lumens (lm)	сст (к)	Beam Angle (°)
	S9046TC/WH	240	9	800/800/850	3000/4000/5700	60
	S9046TC/SN	240	9	800/800/850	3000/4000/5700	60

Dimmable	CRI	Body Colour	Cut Out (mm)	Diameter (mm)	Dim (mm)
YES	80	WHITE	92	103	60(H)
YES	80	SATIN NICKEL	92	103	60(H)


Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling"





Dimensions

Dimensions





THE SFI SYSTEM ELIMINATES LED FLICKERING.

SIMPLY MATCH THE ECOGEM SFI DOWNLIGHT WITH THIS SDD400SFI DIMMER







DIM with FLICKER CONTROL

For related products please scan me



NSW/ACT: 02 9723 3099 QLD: 07 3879 5999 VIC/TAS/SA/NT: 03 9532 3168 WA: 08 9248 7458

