



PLUTO 100FC

Australian approved constant voltage flickerCONTROLLED driver, IP67

Application



An ideal choice for LED strips, LED Neon or exterior lighting requirements

Design Specifications

- SELV and EMC compliant, flickerCONTROLLED performance
- Safe no load operation, power factor 0.9, non-dimmable
- Overload and short circuit protection
- 1.2m flex and plug fitted for easy installation, output (secondary) end is provided with rubber fly leads
- Durable metal casing IP67
- Minimum load 100/12V 1 watt, 100/24V 1 watt Max.
LED Driver Number on MCB C type 16A (for driver >100W) = 23 (12V), 10 (24V)



Technical Specification

Product	Model No.	Input Voltage (V/AC)	Output Voltage (V/DC)	Frequency (Hz)	Power (W)	Power Factor
	PLUTO 100/12V/FC	240	12	50	100	0.95
	PLUTO 100/24V/FC	240	24	50	100	0.95

Dim (mm)
170(L) x 61(W) x 34(H)
170(L) x 61(W) x 34(H)

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with [SAL Terms and Conditions of sale](#) and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".

THE SFI SYSTEM ELIMINATES LED FLICKERING.

**DIMMABLE
CONTROL WITH
SFI FLICKER
CONTROL
TECHNOLOGY**
when paired with
SAL SFI downlights



**DIM with
FLICKER
CONTROL**

For related
products
please
scan me

