



Main

Product or component type	Appliance inlet
Accessory / separate part category	Connection accessory
Product compatibility	Connector Easy56 EY56CSC310
Plug, socket category	Low voltage
Poles description	1P + N + E
Pin number	3 pins
Network type	AC
Outlet standard	Australian/New Zealand

Complementary

Mounting mode	Surface mounted
Plug, socket, control station shape	Straight
[In] rated current	10 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Material	Polycarbonate cover :
Contacts material	Brass pins :
Connections - terminals	Screw terminals
Cable cross section	1.5...6 mm ²
Cable stiffness	Rigid or stranded
Wire stripping length	10 mm
Product weight	0.471 kg
Height	101 mm
Width	101 mm
Depth	102 mm
Colour	Grey (RAL 7035)

Environment

Standards	AS/NZS 60320.1
Quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25...75 °C
Ambient air temperature for storage	-25...75 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1539 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
Product environmental profile	Available Product Environmental
Product end of life instructions	Need no specific recycling operations