



Main

Product or component type	Connector
Accessory / separate part category	Connection accessory
Product compatibility	Plug Easy56 EY56P315
Plug, socket category	Low voltage
Poles description	1P + N + E
Pin number	3 pins
Shape of pin	Flat
Network type	AC
Outlet standard	Australian/New Zealand

Complementary

Plug, socket, control station shape	Straight
[In] rated current	15 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Material	Polycarbonate housing :
Contacts material	Brass sleeves :
Connections - terminals	Screw terminals
Cable cross section	1.5 mm ²
Wire stripping length	12...34 mm
Cable outer diameter	7.4...10.6 mm
Cable entry	Cable gland
Thread type	M20
Product weight	0.107 kg
Height	65 mm
Width	65 mm
Depth	105 mm
Colour	Clear body) Orange (RAL 2004) plug)
Targeted country	New Zealand Australia
Market segment	Industry Small commercial Utility

Environment

Standards	AS/NZS 3120
Quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25...75 °C
Ambient air temperature for storage	-25...75 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1539 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
Product environmental profile	Available Product Environmental
Product end of life instructions	Need no specific recycling operations