



Main

| | |
|---------------------------|------------------------|
| Product name | Easy56 |
| Product or component type | Plug |
| Device short name | EY56P532 |
| Plug, socket category | Low voltage |
| Poles description | 3P + N + E |
| Pin number | 5 pins |
| Shape of pin | Tubular |
| Outlet standard | Australian/New Zealand |

Complementary

| | |
|-------------------------------------|-----------------------------------------|
| Plug, socket, control station shape | Straight |
| [In] rated current | 32 A |
| [Ue] rated operational voltage | 500 V |
| Network type | AC |
| Network frequency | 50 Hz |
| Contacts material | Brass pins : |
| Connections - terminals | Screw terminals |
| Cable cross section | 4...16 mm ² |
| Cable outer diameter | 11...29.5 mm |
| Wire stripping length | 10...65 mm |
| Cable entry | Cable gland |
| Product weight | 0.42 kg |
| Height | 78 mm |
| Width | 78 mm |
| Depth | 176 mm |
| Colour | Orange (RAL 2004) plug Clear body |
| Targeted country | New Zealand Australia |
| Market segment | Utility Industry Small commercial |

Environment

| | |
|---------------------------------------|-----------------------------|
| Standards | AS/NZS 3123 |
| IP degree of protection | IP66 conforming to AS 60529 |
| Ambient air temperature for operation | -25...75 °C |
| Ambient air temperature for storage | -25...75 °C |

Offer Sustainability

| | |
|--------------------------|---------------------------|
| Sustainable offer status | Not Green Premium product |
|--------------------------|---------------------------|