



Main

Product name	Easy56
Device short name	EY56SW332
Product or component type	Switch
Poles description	3P
Control type	Rotary knob
Rotary handle padlocking	2 padlocks x Ø 8 mm

Complementary

[Ue] rated operational voltage	500 V AC 50 Hz
[Ithe] conventional enclosed thermal current	32 A
[Ie] rated operational current	32 A AC-23A at 500 V AC 32 A AC-21A at 500 V AC
Making capacity	320 A at 500 V AC-21A 320 A at 500 V AC-23A
[Icm] rated short-circuit making capacity	1 kA at 500 V (AC-21A) 1 kA at 500 V (AC-23A)
[Icw] rated short-time withstand current	1.5 kA at 500 V duration: 1 s
Breaking capacity	0.2 kA at 500 V (AC-23A) 0.2 kA at 500 V (AC-21A)
Suitability for isolation	Yes
Connections - terminals	Screw terminals cable 1...16 mm ² - cable stiffness: rigid or stranded -
Height	101 mm
Width	101 mm
Depth	101 mm
Product weight	0.471 kg
Colour	Dark grey rotary handle Grey RAL 7035 body
Targeted country	New Zealand Australia
Market segment	Utility Industry Small commercial

Environment

Standards	AS/NZS 3133
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25...75 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------