



## Main

Commercial Status	Commercialised
Range of product	NSX400...630 NSX400...630 DC
Device short name	Motor mechanism module
[In] rated current	400 A 630 A
Control circuit voltage	220...240 V AC 50/60 Hz 208...277 V AC 60 Hz

## Complementary

Control type	Standard
Control signal type	Impulse Maintained
Mounting mode	Fixed
Response time	< 80 ms closing < 600 ms opening
Maximum operating frequency	4 per minute
Power consumption in VA	<= 500 VA opening <= 500 VA closing
Locking options description	1 to 3 padlocks Ø 5 to Ø 8 Padlocking in OFF position

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0908 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations

## RoHS compliance

RoHS EUR status	Compliant
RoHS EUR conformity date(YYYY)	0908

## Contractual warranty

Period	18 months
--------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.