

Product datasheet

Specifications



Acti9, MD Isobar standard distribution board, Acti9, 72 poles, 160A main switch, 18mm, IP56, grey

MD272EM1

Main

Range	Acti9
Product name	Acti9 isobar DB
Device short name	MD
Product or component type	Distribution board
Device application	Distribution
Enclosure type	Weatherproof enclosure
Door type	External plain
Provided equipment	earth/neutral terminal block 165 A pole filler circuit schedule card removable gland plates - top and bottom 2 keys terminal shield TNA chassis enclosure door DIN rail main switch
Colour	Grey

Complementary

[Ue] rated operational voltage	415 V
Network frequency	50 Hz
[Ie] rated operational current	160 A
Breaking capacity	25 kA
[Ui] rated insulation voltage	500 V
[Uimp] rated impulse withstand voltage	6 kV
Enclosure mounting	Surface
Poles description	3P + N
Enclosure material	Steel
Outgoer Pole capacity	72 x 18 mm steel
Height	1200 mm
Width	580 mm

Depth	225 mm
--------------	--------

IP degree of protection	IP56
--------------------------------	------

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Number of Units in Package 1	1
-------------------------------------	---

Package 1 Height	25.0 cm
-------------------------	---------

Package 1 Width	60.0 cm
------------------------	---------

Package 1 Length	125.0 cm
-------------------------	----------

Package 1 Weight	64.0 kg
-------------------------	---------

Recommended replacement(s)