

Catalogue No: **BCO8003PMB**

BYPASS UPS CHANGEOVER SWITCH W/EXTERNAL HANDLE 800A 3P

Power Distribution and Protection > Isolators and Transfer Switches > Transfer Switches > Socomec Manual Transfer Switches > BCO Bypass Manual Transfer Switch > BCO 3 Pole Bypass changeover kits w/external handle



KIT - 800A 3 pole Bypass changeover switch Includes Handle and Shaft

- Standard (I-O-II) and make before break (I-I&II-II) options available covering any application requirement
- Three stable positions (I-O-II) not affected by voltage drops or vibrations ensuring the connected load is protected against possible network interference
- Easy connections thanks to copper bar connection kit accessory for 2000 to 3200A switches enabling the use of flat or edgewise connection with top or bottom bridging.
- Compatibility with the ergonomic IP65 S-Type Handles which features interlocking (in the ON position), pad locking, UV and chemical agent resistive material and the choice of standard blue or red/yellow colour

Representative Photo Only
(actual product may vary based on configuration selections)

SPECIFICATIONS

Component Type Power Distribution & Protection	Manual Changeover Switch
Poles	3
Ui, Rated Insulation Voltage	1000
Uimp, Impulse Withstand Voltage	12
Ie, Rated Operational Current, AC 21a, 690V AC	800
Ie, Rated Operational Current, AC 22a, 690V AC	800
Ie, Rated Operational Current, AC 23a, 690V AC	200
Ie, Rated Operational Current, DC 21a, 220V DC	800
Ie, Rated Operational Current, DC 21a, 440V DC	800
Ie, Rated Operational Current, DC 22a, 220V DC	800
Ie, Rated Operational Current, DC 22a, 440V DC	800
Ie, Rated Operational Current, DC 23a, 220V DC	800
Ie, Rated Operational Current, DC 23a, 440V DC	800
Icw, short time withstand current, 400V, 1s (rms)	26
Ipk, Peak Current, Max, 400V	55000
Current, Fuse-Protected Short-Circuit Capacity, 400V	50
Mechanical service life	3000
Weight	47
Cable Cross Section (Min)	2 x 185 mm ²
Cable Cross Section (Max)	2 x 300 mm ²
Standards Compliance	IEC 60947-3

