

Catalogue No: **CAT7N-5.5P-415VAC**

STARTER DOL 5.5kW START/STOP 415V AC CONTROL NO OVERLOAD

Motor Control and Drives > Motor Starting and Protection > Assembled Motor Starters > Sprecher + Schuh Motor Starters > Direct On Line (DOL) Motor Starters > CAT7N DOL Starters 5.5 to 18.5kW



Representative Photo Only
(actual product may vary based on configuration selections)

Direct On-Line Starter 5.5KW, IP66 Polycarbonate Enclosure, Controlvoltage 415 V AC, Start, Stop Pushbuttons, No Overload

- IP66 ABS V0 insulated enclosure for high ingress protection
- Complete with choice of stop, start and reset pushbuttons to match your application requirements
- 5.5 to 7.5kW: choice of CT7N thermal overload or CEP7 electronic overload (ordered separately)
- 11 to 18.5kW: wide current setting range (5:1) from included CEP7 electronic overload for convenience and flexibility

SPECIFICATIONS

| | |
|---|--|
| kW Rating, AC-3, 415V | 5.5 kW @415V |
| Component Type Motor Control and Drives | DOL Starter |
| Motor FLC, Min | 0.1 A, min |
| Motor FLC, Max | 12.5 A, max |
| IP Rating | IP66 |
| Motor Connection | 3 wire |
| Enclosure Type | Insulated polycarbonate enclosed (IP 66) |
| Control Voltage | 415 V AC |
| Button Arrangement | Start / Stop |

REFERENCES

| | |
|---|---|
| IECEx Certificate | - |
| Supplier Declaration of Conformity: | - |
| Installation Guide: | - |
| User Manual: | - |
| Manufacturer Datasheet: | - |
| Manufacturer Catalogue & Product Selection: | - |

Catalogue No: **CAT7N-5.5P-415VAC**

STARTER DOL 5.5kW START/STOP 415V AC CONTROL NO OVERLOAD

Motor Control and Drives > Motor Starting and Protection > Assembled Motor Starters > Sprecher + Schuh Motor Starters > Direct On Line (DOL) Motor Starters > CAT7N DOL Starters 5.5 to 18.5kW



Technical Diagram