
































## Prolec

Dimensions in MM

Slow Acting	Ampere
Part Number	Rating
SWE-515DA.125	125mA
SWE-515DA.250	250mA
SWE-515DA.350	350mA
SWE-515DA.375	375mA
SWE-515DA.500	500mA
SWE-515DA.600	600mA
SWE-515DA.750	750mA
SWE-515DA001	1A
SWE-515DA1.25	1.25A
SWE-515DA01.5	1.5A
SWE-515DA01.6	1.6A
SWE-515DA002	2A
SWE-515DA2.25	2.25A
SWE-515DA02.5	2.5A
SWE-515DA003	3A
SWE-515DA03.5	3.5A
SWE-515DA004	4A
SWE-515DA005	5A
SWE-515DA006	6A
SWE-515DA007	7A

ELECTRONIC

**I.R.:** 35A at 250VAC (125mA to 1A)  
100A at 250VAC (1.25A to 3A)  
400A at 125VAC (3.5A to 7A)  
**Voltage:** 250VAC (125mA to 3A),  
125VAC (3.5A to 7A)  
**Pack Size (bag):** 10, 100, 1500  
**Holders:** Contact sales for further information.  
**Notes:** Also available in pigtail version (loose, tape and reel format). Imperial dimensions: 0.59" x 0.2"  
**Approvals Available:**                                  

**Bel Fuse**  
**Fast / Slow / Surge Withstand**



Figure 1 shows the dimensions of the test specimen. The specimen is a cylindrical rod with a central section of length 15 mm and a diameter of 5.5 mm. The total length of the specimen is 38.1 mm. The dimensions are given in mm.

These fuse ranges are available in a variety of pack sizes. They can be ordered loose (bulk) or on tape & reel. Please contact sales for more information.