


3AB 600V / 440V CERAMIC FUSES

Prolec
Fast Acting, Type (F)

500V Version Part Number	600V Version Part Number	Ampere Rating
SWE-3AB-FB.160	—	160mA
SWE-3AB-FB.200	SWE-3AB-FB.200/600V	200mA
SWE-3AB-FB.250	—	250mA
SWE-3AB-FB.315	—	315mA
SWE-3AB-FB.400	—	400mA
SWE-3AB-FB.500	SWE-3AB-FB.500/600V	500mA
SWE-3AB-FB.630	—	630mA
SWE-3AB-FB.800	SWE-3AB-FB.800/600V	800mA
SWE-3AB-FB001	SWE-3AB-FB001/600V	1A
SWE-3AB-FB1.25	—	1.25A
SWE-3AB-FB01.6	—	1.6A
SWE-3AB-FB002	SWE-3AB-FB002/600V	2A
SWE-3AB-FB02.5	—	2.5A
	SWE-3AB-FB003/600V	3A
SWE-3AB-FB3.15	—	3.15A
SWE-3AB-FB004	—	4A
SWE-3AB-FB005	SWE-3AB-FB005/600V	5A
SWE-3AB-FB06.3	—	6.3A
SWE-3AB-FB007	SWE-3AB-FB007/600V	7A
SWE-3AB-FB008	—	8A
SWE-3AB-FB010	SWE-3AB-FB010/600V	10A
SWE-3AB-FB12.5	—	12.5A
SWE-3AB-FB015	—	15A
SWE-3AB-FB016	—	16A
SWE-3AB-FB020*	—	20A
SWE-3AB-FB025*	—	25A



Dimensions in MM

Additional I.R Information

50kA at 500VAC (160mA to 6.3A)

1.5kA at 500VAC (8A to 16A)

1.5kA at 440VAC (20A to 25A)

20kA at 400VDC (160mA to 6.3A).

50kA at 600VAC (200mA to 10A)

Pack Size (bag): 100, 1000

Holders: Clips (p110-111), Inline (p121)

Imperial Dimensions: 1 1/4" x 1/4"

Notes: *440VAC Only.


Approvals: RoHS Optional

Axial leaded versions also available.
See page 148 for further information.

3AB 500V / 250V CERAMIC FUSES

Siba
Slow Acting, Type (T)

500V Version Part Number	Ampere Rating	Voltage
SWE-3ABDA.100/500V	100mA	500VAC
SWE-3ABDA.125/500V	125mA	500VAC
SWE-3ABDA.160/500V	160mA	500VAC
SWE-3ABDA.200/500V	200mA	500VAC
SWE-3ABDA.250/500V	250mA	500VAC
SWE-3ABDA.315/500V	315mA	500VAC
SWE-3ABDA.400/500V	400mA	500VAC
SWE-3ABDA.500/500V	500mA	500VAC
SWE-3ABDA.630/500V	630mA	500VAC
SWE-3ABDA.800/500V	800mA	500VAC
SWE-3ABDA001/500V	1A	500VAC
SWE-3ABDA1.25/500V	1.25A	500VAC
SWE-3ABDA01.6/500V	1.6A	500VAC
SWE-3ABDA002/500V	2A	500VAC
SWE-3ABDA02.5/500V	2.5A	500VAC
SWE-3ABDA3.15/500V	3.15A	500VAC
SWE-3ABDA004/500V	4A	500VAC
SWE-3ABDA005/500V	5A	500VAC
SWE-3ABDA06.3/500V	6.3A	500VAC
SWE-3ABDA008/500V	8A	500VAC
SWE-3ABDA010/500V	10A	500VAC
SWE-3ABDA12.5/500V	12.5A	500VAC
SWE-3ABDA016/500V	16A	500VAC
SWE-3ABDA020/440V	20A	440VAC
SWE-3ABDA025/440V	25A	440VAC
SWE-3ABDA032/250V	32A	250VAC



Dimensions in MM

I.R.: 1500A at rated VAC

10kA at 440VAC (100mA to 10A)

1.5kA at 400VDC

Voltage: 500VAC (100mA to 16A)

440VAC (20A to 25A)

250VAC (32A)

Pack Size (bag): 100, 1000

Holders: Clips (p110-111), Inline (p121)

Approvals: RoHS