



8.5 X 31.5MM CERAMIC FUSES

ETI / Bussmann / dF
Fast & Slow Acting

Fast Acting Type gG/gL	Slow Acting Type aM	Ampere Rating
Part Number	Part Number	
SWE-C-NB.500	–	500mA
SWE-C-NB001	SWE-C-SB001	1A
SWE-C-NB002	SWE-C-SB002	2A
SWE-C-NB004	SWE-C-SB004	4A
SWE-C-NB006	SWE-C-SB006	6A
SWE-C-NB008	SWE-C-SB008	8A
SWE-C-NB010	SWE-C-SB010	10A
SWE-C-NB012	SWE-C-SB012	12A
SWE-C-NB016	SWE-C-SB016	16A
SWE-C-NB020	SWE-C-SB020	20A
SWE-C-NB025	SWE-C-SB025	25A

I.R.: 20kA at 400VAC
Voltage: 400VAC
Pack Size (box): 10
Holders: Din Rail Mount (please call)

Approvals: IEC 



Dimensions in MM

INDUSTRIAL

10.3 X 38.1MM CERAMIC FUSES

ETI / Bussmann / dF
Fast & Slow Acting

Fast Acting Type gG/gL	Slow Acting Type aM	Ampere Rating
Part Number	Part Number	
SWE-CH10-NB.500	SWE-CH10-SB.500	500mA
SWE-CH10-NB001	SWE-CH10-SB001	1A
SWE-CH10-NB002	SWE-CH10-SB002	2A
SWE-CH10-NB004	SWE-CH10-SB004	4A
SWE-CH10-NB006	SWE-CH10-SB006	6A
SWE-CH10-NB008	SWE-CH10-SB008	8A
SWE-CH10-NB010	SWE-CH10-SB010	10A
SWE-CH10-NB012	SWE-CH10-SB012	12A
SWE-CH10-NB016	SWE-CH10-SB016	16A
SWE-CH10-NB020	SWE-CH10-SB020	20A
SWE-CH10-NB025	SWE-CH10-SB025	25A
SWE-CH10-NB032	SWE-CH10-SB032	32A

I.R.: 120kA at rated voltage
Voltage (gG): 500VAC (500mA to 25A)
 400VAC (32A)
Voltage (aM): 500VAC (500mA to 16A)
 400VAC (20A to 32A)

Pack Size (box): 10
Holders: Clips (p111)
 Blocks (p132)
 Panel (p119)
 Carrier (p126-128)
 Inline (p123)
 Disconnect (p141)

Approvals: IEC 



Dimensions in MM