

Catalogue No: **ZS125M4100TF**

TBP ELCB 125 FRAME 65kA 4P 100A 30mA-3A ADJ TH FIX MG

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > TemBreak PRO Moulded Case Circuit Breaker > TemBreak PRO Earth Leakage > ZS Model 125 AF



Representative Photo Only
(actual product may vary based on configuration selections)

- Earth leakage protection ELCB for Power distribution or motor start applications
- Current limiting, lowers fault let through energy
- Direct opening main contact / toggle mechanism
- Complies to AS / NZ 60947-2, IEC 60947-2, AS / NZS 2081 and CE
- Panel mount standard, with other mounting options
- Full range of accessories for application flexibility
- 3 or 4 pole versions
- Fault interruption rating; 65 kA

SPECIFICATIONS

Switching Poles	3P + N
Utilisation Category	A
Type of Power Supply	AC AC/DC
Component Type MCCB	Earth Leakage CB
AC Power loss per pole at full rated current	9 W
I _r , Thermal Trip Current, Min	63 A
I _r , Thermal Trip Current, Max	100 A
I _m , Magnetic Trip Current	1200 A
Storage Temperature, Min	-10 °C min
Storage Temperature, Max	70 °C max
General Accessories	Alarm Switch Auxiliary Switches Handle Operators Interpole Barriers Locking Devices Motor Operator Shunt Trip Terminal Covers Under Voltage Trip
Vibration Acceleration (Max.)	19 m/s ²
Vibration Frequency, Operational (Max.)	16.7 Hz
Vibration Duration (Max.)	12 min
Standards Compliance	AS/NZS 2081 IEC 60947-2
Certifications	CE DEKRA RCM
Shipping Approvals	Contact NHP

Catalogue No: **ZS125M4100TF**

TBP ELCB 125 FRAME 65kA 4P 100A 30mA-3A ADJ TH FIX MG

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > TemBreak PRO Moulded Case Circuit Breaker > TemBreak PRO Earth Leakage > ZS Model 125 AF



REFERENCES

IECEx Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: -