

Quick Overview

LED Canopy Light



Features

Features & Benefits

- Aluminum housing powder coated white
- Tempered glass lens and polycarbonate cover
- Selectable wattage 36-75-100-120w
- Dip switch function for colour temperature change
- Slim body design
- Constant current driver
- Surge protected 6kV Line-Line, 10kV Line-Earth
- High efficiency SMD chip 150Lm/w
- Operating Temp: -30°C to +50°C
- IP65 rated at IK08 impact resistance

Installation Options

- Plug-in microwave or PIR sensor
- 501 x 491 x 17mm adaptor plate

Details

Part No.	TSTSCP01
Brand	TRADESAVE
Pack Quantity	1

Proudly Distributed By



1300 555 586
www.repelec.com.au

Sign up or log in to repelec.com.au
[f](#) [@](#) [v](#) [@RepelecAU](#)

Unit Of Measure	Each
Voltage AC	200-240V
Watt	36-120W
PF	0.95
CCT	3K-4K-5K
Ra	70
Lifetime (hrs)	63,000
Lumens	5400-11250-15000-18000
Beam Angle	120°
Fitting Colour	White
Dimensions (W x H x D) mm	368 x 368 x 61
Operating Temperature	-30°C to +50°C
IK Rating	IK08
Ingress Protection Rating	IP65
Weight (kg)	2.8