




## MAXILED XLC10


10 Watts / 1130 Lumens / 85+ CRI



10W Recessed fixed LED downlight range with dual reflector design to produce a low UGR rating of <19. Available in 3000K and 4000K colour temperature options. Large pressure cast aluminium heatsink provides effective thermal management ensuring high output and long lifespan. Supplied with remote driver.



105



110



95-100mm

System Power 11.7W

LED Power 10.5W

IP Rating IP20

Cut-Out 95-100mm

Weight 650g

	3000K	4000K
COB Lumen Output	1090 lm	1130 lm
Total Luminous Flux	903 lm	938 lm

Efficacy	80.17 lm/W 4000K	Lifetime	50,000hrs (L80)		
Dimming	Leading + Trailing Edge		Optional: Dali 1-10v		
Input Voltage	100V - 240V AC 50/60 Hz	Protection	Thermal and Short Circuit	Power Factor	> 0.9

Product	CCT	Beam Angle	Trim Colour	Driver
XLC10	3000K 3 4000K 4	Medium Beam MB	White W	Leading + Trailing DALI* DALI 1-10v* 1-10
XLC10	3	MB	W	

XLC103-MB-W

\* Optional



**TREND**  
LIGHT BY SOLID STATE

Level 3, 290-292 Coward Street, Mascot, NSW, 2020

Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au