



OXYGEN FREE COPPER

RoHS compliant

V90 PVC Insulated

50V AC or 120V DC

SINGLE CORE LOW TENSION PRIMARY WIRING



Applications: General Purpose Automotive Wiring

Conductor: OXYGEN FREE Plain Copper Wire to AS/NZS 1125

Insulation: V90 P.V.C. to AS/NZS 3808

Colours: Black, Blue, Brown, Green, Grey, Orange, Pink, Red, Violet, White, Yellow and the widest range of trace colours

Packs: 30, 100, 500, 1000 metres - *other packs by request*

CODE	*MM INDUSTRY EQUIVALENT	NZ EQUIV.	CONDUCTOR NO/DIA (mm)	NOMINAL AREA (mm ²)	**AMP RATING @ 30°C	INSULATION THICKNESS (mm)	ELECTRICAL RESISTANCE @ 20°C (ohm/km)	NOMINAL O.D. (mm)	MASS (kg/100m)	STOCK ITEM
ARM18032	2.5	148	8/0.32	0.64	13	0.4	29.9	2.0	0.9	
ASC11603	3	150	14/0.32	1.13	20	0.4	16.5	2.2	1.4	✓
ASC12603	4	152	23/0.32	1.84	28	0.4	10.1	2.6	2.1	✓
ASC14103	5	154	36/0.32	2.90	37	0.4	6.4	3.0	3.3	✓
ASC16503	6	156	57/0.32	4.59	48	0.6	4.1	4.0	5.3	✓