




COPPER CONDUCTOR TERMINATIONS



COPPER CRIMP LINKS

- Solid drawn copper tube
- Centre dimples • Ends reamed



DESCRIPT.	CAT NO.	CONDUCTOR AREA mm ²	STRANDING METRIC	DIMENSIONS mm		NO. OF CRIMPS (TOOL NO.)							CRIMPING DIE
				A	I.D.	00	18	20	21	22	38A	40B	
CK0.5	H1451	0.5	1/0.80	22	2.1	2	-	-	-	-	-	-	
CK02.5	H1467	2.5	7/0.67	22	2.5	2	-	-	-	-	-	-	
CK4	H1452	4	7/0.85	22	3.3	2	1	-	-	-	-	-	
CK6	H1453	6	7/1.04	22	3.7	2	1	-	2	2	1	-	38-44CU
CK10	H1454	10	7/1.35	22	4.7	2	1	-	2	2	1	-	38-57CU
CK16	H1455	16	7/1.70	44	5.5	-	3	2	2	2	1	-	38-63CU
CK20	H1456	20	19/0.44	44	6.3	-	-	2	2	2	1	-	38-70CU
CK25	H1458	25	19/1.35	48	7.1	-	-	2	2	2	1	-	38-77CU
CK35	H1488	35	19/1.53	48	8.4	-	-	2	2	2	1	-	38-92CU
CK50	H1460	50	19/1.78	48	9.5	-	-	2	2	2	1	-	38-104CU
CK70	H1461	70	19/2.14	51	11.0	-	-	2	-	2	1	-	38-115CU
CK95	H1462	95	37/1.78	54	13.4	-	-	2	-	2	1	1	38-142CU
CK120	H1492	120	37/2.03	65	15.5	-	-	-	-	2	2	1	38-165CU
CK150	H1493*	150	37/2.25	65	16.3	-	-	-	-	-	2	1	38-183CU
CK185	H1494	185	37/2.52	65	18.4	-	-	-	-	-	2	1	38-200CU
CK240	H1495	240	61/2.25	89	21.2	-	-	-	-	-	3	1	38-231CU
CK300	H1496	300	61.2.52	89	23.8	-	-	-	-	-	3	1	38-260CU
CK400	H1470	400	61/2.85	89	26.8	-	-	-	-	-	-	1	40-281CU
CK500	H1471	500	61/3.20	114	30.0	-	-	-	-	-	-	2	40-310CU
CK630	H1499*	630	127/2.52	114	33.5	-	-	-	-	-	-	2	40-370CU
CK800	H1474	800	127/2.85	230	39.3	-	-	-	-	-	-	3	40-432CU
CK1000	H1475	1000	127/3.20	230	43.8	-	-	-	-	-	-	3	40-480CU

All sizes of crimp links are compatible with imperial size cables except those marked*



Tyco Electronics

Our commitment. Your advantage.